



Measure solutions **Measure solutions** **Measure solutions**



SOLUTIONS

2011 General Catalogue - Rev.0



Industrial processes

3



Drinkable water
Waste treatment
Food and beverage
Cement works
Paper mills
Chemicals
Energy
Cereals and mills
Plastics


Symbols




..... **Level continuous measure**




..... **ON-OFF level control**




..... **Open channel flow measure**



..... **Open channel flow control**



..... **Full pipe flow measure**




..... **Full pipe flow control**



..... **Pressure measure**



..... **Differential pressure measure**



..... **Temperature profile monitor**

LEVEL CONTINUOUS MEASURE - Ultrasonic

METER , IP67 level transmitter with internal display, 0,25÷5m/0,4÷8m	page	7
SMART , IP66÷68 level transmitter with 2 relays built-in, 0,25÷5m/0,4÷7m	page	8
521SMART , IP65 level transmitter with 2 relays built-in, 0,4÷10m	page	9
522SMART , IP65 level transmitter with 2 relays built-in, 0,6÷15m	page	10
SWING , IP66 Level, differential level, flow and pumps control unit	page	11
VLW601 , IP67 Display and control unit, coupled with METER and PTU51 transmitters	page	12
PTU51 , IP68 level transmitter, 0,3÷6m	page	13
PTU05 , IP68 level transmitter, 0,3÷5m	page	14
PTU10 , IP68 level transmitter, 0,4÷8m	page	15
PTU15 , IP68 level transmitter, 0,7÷12m	page	16
UA , Ultrasonic system accessories	page	17

LEVEL CONTINUOUS MEASURE - Pulse Radar

RPL51 , IP67 level transmitter, working p. -1,0÷3bar, max. 30m	page	18
RPL52 , IP67 level transmitter, working p. -1,0÷16bar, max. 30m	page	20
RPL53 , IP67 level transmitter, working p. -1,0÷40bar, max. 30m	page	22
RPL54 , IP67 level transmitter, working p. -1,0÷40bar, max. 70m	page	24
RPL55 , IP67 level transmitter, working p. -1,0÷3bar, max. 10m	page	26
RPL56 , IP67 level transmitter, working p. -1,0÷40bar, max. 30m	page	28
RPL58 , IP67 level transmitter, working p. -1,0÷16bar, max. 70m	page	30

LEVEL CONTINUOUS MEASURE - Guided Wave Radar

RWL51 , IP67 level transmitter, working p. -1,0÷40bar, max 3m/25m	page	32
RWL52 , IP67 level transmitter, working p. -1,0÷40bar, max 3m	page	34
RWL53 , IP67 level transmitter, working p. -1,0÷40bar, max 3m	page	35
RWL54 , IP67 level transmitter, working p. -1,0÷40bar, max 3m/30m	page	36

LEVEL CONTINUOUS MEASURE - Capacitive

CLT4 , Rod probe	page	38
CLT5 , Double rods probe	page	40
CLT7 , Rope probe for granulate	page	42
CLT8 , Rope probe for liquids	page	44

LEVEL CONTINUOUS MEASURE - Level air purge system

PVI , Level transmitter unit, output 4÷20mA and 0÷10V + 4 relays	page	46
PTS , Level transmitter unit, output 4÷20mA or 0÷10V + 1÷2 relays	page	47

LEVEL CONTINUOUS MEASURE - Display and control units

LC2 , Switch and power control unit for transmitters	page	48
VL501 , 4÷20mA Loop powered digital display	page	48
VLW501 , IP66 4÷20mA loop powered digital display	page	48

SLA2X , Display and control unit, input 4÷20mA, max. 4 relays	page	49
CVI , IP10 control and power supply unit with 4 relays, input 4÷20mA	page	50
A2S , 2 relays control unit, input 4÷20mA	page	51
 CONTROLLO DI LIVELLO ON-OFF - Principio capacitivo		
CLS2 , Standard rod level switch (250mm)	page	52
CLS4 , Rod level switch, max 3m	page	54
CLS7 , Rope level switch for granulates	page	56
CLS8 , Rope level switch for liquids	page	58
CLS9 , Rod level switch for plastic tanks	page	60
 ON-OFF CONTROL LEVEL - Conductive electrodes		
CLN , Electrode for well and borehole	page	61
PS33 , 3 316SS rods electrode, L = 300mm, PVC electrode holders	page	61
PS310 , 3 316SS rods electrode, L=1000mm, PVC electrode holders	page	61
SL , PTFE insulated electrode, L=300÷1000mm, Pmax=10bar	page	61
SU , PTFE insulated electrode, L=56mm, P=25bar	page	62
RL2 , PTFE insulated electrode, L=105mm	page	62
RL3 , Multi rods electrode, 3/5 rods	page	62
RL5 , Ceramic insulated electrode with fibre glass, L=65mm	page	62
RL6 , Multi rods electrode, max. 5 aste	page	63
RL8 , Multi ropes electrode, max. 5 funi	page	64
 ON-OFF CONTROL LEVEL - Control units for conductive electrodes		
RAL04 , Unit to control up to 4 setpoints; 4 relays	page	65
RAL11 , Min/Max level control or pump control; 2 relays, sensibility adj.	page	65
RAL12 , Min/Max lev. c./pump c.; 2 rel. with interruption cables control, sens. adj.	page	66
RAL13 , Min/Max level control or pump control; 2 relays, sensibility and delay adj	page	66
 ON-OFF CONTROL LEVEL - Vibration		
RSL200 , Diapason level switch for granulate and powder	page	67
RSL201 , Vibrating rod level switch for granulate and powder	page	68
 ACCESSORIES - For capacitive,conductive and vibration probes		
CRA , Capacitive and conductive system accessories	pagina	69
CRSP , Capacitive, conductive and vibration spare parts	page	70
 OPEN CHANNEL FLOW MEASURE		
FLOWMETER , Ultrasonic compact control unit	page	71
OC 1000 , Control unit	page	72
BS , Venturi flumes	page	73
PB , Palmer-Bowlus flumes	page	76
CAL , Out of standard weirs and flumes, flow calculation	page	76

Index: *measure&controls*

FULL PIPE FLOW MEASURE - Electromagnetic

RPmag62 , In conductive fluids in water or wastewater	page	77
Smag62 , In conductive fluids, DIN11851 sanitary connections	page	80
Pmag62 , In conductive fluids in water or wastewater	page	82
MSP , Electromagnetic flow meter spare parts	page	84
MA , Electromagnetic flow meter system accessories	page	85

FULL PIPE FLOW MEASURE - Ultrasonic

SGM-100F , Wall mounting unit with clamp-on or insertion transducers	page	86
SGM-100H , Battery portable unit with clamp-on transducer	page	88
SGM-100T , Ultrasonic Thickness Gauge	page	89
TTA , Accessories and spare parts for transit time flow meters	page	90

TOTAL FLOW INDICATOR

SLM2X , Total flow indicator with analog input	page	91
SLM2XH3 , Total and instantaneous flow rate indicator with analog input	page	91

PRESSURE MEASURE

P-8 , Compact transmitter	page	92
P-8J , Compact transmitter	page	95
P-K1 , "General purpose" transmitter + display	page	96
P-L , Hydrostatic level head transmitter	page	99
PAK , HART pressure transmitter	page	101
P-BADP , "General purpose" differential pressure transmitter	page	103
P-BADR , Low ranges differential pressure transmitter	page	105
PA , pressure and differential pressure systems accessories	page	106

TEMPERATURE CONTINUOUS MEASURE - Silos temperature profile monitor

AGRITHERM3 , Manual display unit for small plants	page	107
AGRITHERM10 , Temperature display and control unit; 2 relays, IP40	page	107
AGRITHERM20 , Temperature display and control unit; 5 relays, IP66	page	108
AGRITHERM40 , PC based for temperature display and control, for control-room	page	108
MUX , Concentrator suitable for up to 8 TT rope probes connection	page	110
TT , Digital multipoints temperature rope probe	page	111
TA , AGRITHERM systems accessories	page	112
TSP , AGRITHERM systems spare parts	page	112



METER

Ultrasonic level transmitter


Ultrasonic - 4÷20mA output

G 2" A / PP threaded connection (for ATEX version in PVDF)

Setting by keyboard/graphic LCD display detachable module (optional)

Temperature range : -30° ÷ +70°C (80° non continuous)

Version	
-	2-wire, range 5m, HART, ATEX II 1/2G Ex ia II C T6 (amb. temp. -20÷+60°C)
0	2-wire, range 8m, HART, ATEX II 1/2G Ex ia II C T6 (amb. temp. -20÷+60°C)
1	2-wire, range 5m
2	2-wire, range 5m, HART
3	2-wire, range 5m, ATEX II 1/2G Ex ia II C T6 (amb. temp. -20÷+60°C)
4	4-wire, range 5m, 2 relays, MODBUS
5	2-wire, range 8m
6	2-wire, range 8m, ATEX II 1/2G Ex ia II C T6 Tamb -20÷+60°C
7	2-wire, range 8m, HART
8	4-wire, range 8m, 2 relays, MODBUS
9	Special
Housing material	
F	PC with transparent cap, IP67
U	Aluminum with transparent cap, IP67 (necessary for ATEX versions)
Z	Special
Power supply	
4	24Vdc (20÷30Vdc)
5	12Vdc (20Vdc) range 5m (only for version 1)
9	Special
Optional (opt.)	
A	None
C	DN80 PN6 UNI 1092-1/PP flange
D	VL601 keyboard/display programming module (395A002D)
H	2" BSP/ PP fixing bolt
S	MODBUS communication software (010F105A)
T	HART communication software (010E105A)
Z	Special



F Housing cod.




PP sensor



U Housing cod.



PVDF sensor



Ultrasonic




SMART

Level control and measure unit


Ultrasonic - G 2" A/PP threaded connection
 4÷20mA output with 2 relays for alarms or pumps control
 Calibration by 2 push-buttons or via RS485 by PC
 Working temperature: -30 ÷ +70°C

Version	
1	IP66, range 0,25÷5m, with electrical connection by 2 internal plug-in connectors
2	IP68, range 0,25÷5m, with n.2 electrical cable (3m length) connection
3	IP66, range 0,4÷7m, with electrical connection by 2 internal plug-in connectors
4	IP68, range 0,4÷7m, with n.2 electrical cable (3m length) connection
5	IP66, range 0,25÷5m, with electrical connection by 2 internal plug-in connectors suggested for installation into calm-pipes
9	Special
Housing material	
B	PP polypropylene
Z	Special
Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz
4	24Vdc
5	12Vdc Attention! Max 3m distance-no relays inside
9	Special
Optional (opt.)	
A	None
C	DN80 PN6 UNI 1092-1 / PP flange
E	IP66 Junction-box for remote calibration (programming push-buttons built in)
F	S/W for communication with SGM LEKTRA ultrasonic units (010D034A)
H	Couple of fixing bolts 2" BSP in PP (620A004T)
Z	Special



Level measurement

Level control






521SMART Level control and measure unit

Ultrasonic - designed for liquids and bulk-solids (max 5m)
 Range: 0,6÷10m; Mechanical protection IP65
 4÷20mA output with 2 relays for alarms or pumps control
 Calibration by 2 push-buttons or via RS485 by PC
 Working temperature: -30 ÷ +70°C

Version	
1	G2"½ (G 2 ½ A) bracket mechanical connection
2	Flanged DN150 PN6 UNI 1092-1 / PP
9	Special
Housing material	
D	PBT + PP (Polypropilene)
Z	Special
Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz
4	24Vdc
9	Special
Optional (opt.)	
A	None
E	IP66 Junction-box for remote calibration (programming push-buttons built-in)
F	PC S/W for the communication to the SGM LEKTRA ultrasonic units (010D034A)
Z	Special






522SMART

Level control and measure unit

Ultrasonic - designed for liquids and bulk-solids (max. 8m)
 Range: 0,7÷15m; Mechanical protection IP65
 4÷20mA output with 2 relays for alarms or pumps control
 Calibration by 2 push-buttons or via RS485 by PC
 Working temperature: -30 ÷ +70°C

Version	
1	G2"½ (G 2 ½ A) bracket mechanical connection
2	Flanged DN150 PN6 UNI 1092-1 / PP
9	Special
Housing material	
D	PBT - PP (Polypropilene)
Z	Special
Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz
4	24Vdc
9	Special
Optional (opt.)	
A	None
E	IP66 Junction-box for remote calibration (programming push-buttons built-in)
F	PC S/W for the communication to the SGM LEKTRA ultrasonic units (010D034A)
Z	Special







Ultrasonic

SWING

Level, open channels flow and pumps control unit

Directly connectable to PTU/SMART ultrasonic sensors
Matrix 58 x 31mm backlit LCD display
5 calibrating push-buttons
IP66 mechanical protection; temperature range : -20 ÷ +60°C

Version	
2	For connection up to 2 PTU/SMART family sensors
3	For very low-power consumption self-switch-off 1 sensor connection
9	Special
Relay	
A	None
C	5 Relays with change over contact (SPDT)
Power supply	
0	115Vac 50÷60Hz
1	230Vac 50÷60Hz
2	24Vac 50÷60Hz
4	24Vdc
Output	
A	None
B	n.1 4÷20mA
C	n.2 4÷20mA
Field Bus	
0	None
1	RS485 (SWING "Pump Control" not available in this version)
9	Special
Accessories	
A	None
S	RS485 communication software (010D038A)






VLW601

IP67 protection
Suitable for METER and PTU51 transmitters

Version	
A	Standard
Z	Special
Power supply	
0	24Vac 50+60Hz
1	115Vac 50+60Hz
2	230Vac 50+60Hz
4	24Vdc
9	Special
Accessories	
A	None
Z	Special





Ultrasonic


13

PTU51

Level transmitter

Ultrasonic - for measurement in liquids, muds and acids;
Range: 0,3 ÷ 6m
Calibration via MODBUS or by VLW601 module
PP enclosure; IP68 proof; power supply 24Vdc
Temperature range -25 ÷ +75°C

Version	
C	Designed to be connected to Swing unit + male connector
D	4÷20mA + MODBUS output transmitter + male connector
Z	Special
Process connection / Sensor material	
0	G 1" A / PP
1	DN100 PN6 UNI 1092-1 / PP flange
2	G 1" A / PVDF
3	DN100 PN6 UNI 1092-1 flange / PVDF
9	Special
Optional (opt.)	
A	None
F	MODBUS PC communication S/W
O	5m linking cable for IP69K connection
P	10m linking cable for IP69K connection
R	15m linking cable for IP69K connection
S	20m linking cable for IP69K connection
T	5m linking cable for IP68 connection
U	10m linking cable for IP68 connection
V	15m linking cable for IP68 connection
W	20m linking cable for IP68 connection
Z	Special






PTU05

Level transmitter

Ultrasonic - for measurement in liquids, muds and acids; range 0,3 ÷ 5m
 Calibration by 2 remote push-buttons or via RS485 by PC
 PP enclosure; IP68 proof; power supply 24Vdc
 Temperature range -25 ÷ +75°C

Version	
A	Designed to be connected to Swing unit (RS485) with 3m linking cable
B	4÷20mA + RS485 output transmitter with 3m linking cable
C	Designed to be connected to Swing unit (RS485) + IP67 male connector
D	4÷20mA + RS485 output transmitter + IP67 male connector
Z	Special
Process connection	
0	G 1" A / PP
1	DN100 PN6 UNI 1092-1 / PP flange
9	Special
Optional (opt.)	
A	None
E	IP66 Junction-box for remote calibration (programming push buttons built-in)
F	PC communication S/W (010D034A)
O	IP67 female connector with 5m linking cable; for C and D version connection
P	IP67 female connector with 10m linking cable ; for C and D version connection
R	IP67 female connector with 15m linking cable ; for C and D version connection
S	IP67 female connector with 20m linking cable ; for C and D version connection
Z	Special





PTU10



Level transmitter

Ultrasonic - for measurement in liquids, muds and acids; range 0,4 ÷ 8m
Calibration by 2 remote push-buttons or via RS485 by PC
PP enclosure; IP68 proof; power supply 24Vdc
Temperature range -25 ÷ +75°C

Version	
A	Designed to be connected to Swing unit (RS485) with 3m linking cable
B	4÷20mA + RS485 output transmitter with 3m linking cable
C	Designed to be connected to Swing unit (RS485) + IP67 male connector
D	4÷20mA + RS485 output transmitter + IP67 male connector
Z	Special

Process connection	
0	G 1" A / PP
1	DN100 PN6 UNI1092-1 / PP flange
9	Special

Optional (opt.)	
A	None
E	IP66 Junction-box for remote calibration (programming push buttons built-in)
F	PC communication S/W (010D034A)
O	IP67 female connector with 5m linking cable; for C and D version connection
P	IP67 female connector with 10m linking cable; for C and D version connection
R	IP67 female connector with 15m linking cable; for C and D version connection
S	IP67 female connector with 20m linking cable ; for C and D version connection
Z	Special






PTU15

Level transmitter

Ultrasonic - for measurement in liquids, muds and acids; range 0,7 ÷ 12m
 Calibration by 2 remote push-buttons or via RS485 by PC
 PP enclosure; IP68 proof; power supply 24Vdc
 Temperature range -25 ÷ +75°C

Version	
A	Designed to be connected to Swing unit (RS485) with 3m linking cable
B	4÷20mA + RS485 output transmitter with 3m linking cable
C	Designed to be connected to Swing unit (RS485) + IP67 male connector
D	4÷20mA + RS485 output transmitter + IP67 male connector
Z	Special
Process connection	
0	G 1" A / PP
1	DN150 PN6 UNI 1092-1 / PP flange
9	Special
Optional (opt.)	
A	None
E	IP66 Junction-box for remote calibration (programming push buttons built in)
F	PC communication S/W (010D034A)
O	IP67 female connector with 5m linking cable; for C and D version connection
P	IP67 female connector with 10m linking cable; for C and D version connection
R	IP67 female connector with 15m linking cable; for C and D version connection
S	IP67 female connector with 20m linking cable; for C and D version connection
Z	Special







UA

Ultrasonic system accessories

Optional (opt.)	
010D034A	RS485 communication S/W for SMART/PTU
010D038A	RS485 communication S/W for SWING (master)
010E105A	HART communication S/W for METER
010F105A	MODBUS RTU communication S/W for METER
010F119A	MODBUS RTU communication S/W for FLOWMETER
395A002D	Keyboard/display module VL601 for radar and ultrasonic
420A008B	IP66 Junction-box for remote calibration (programming push bottoms built in)
420D067B	Swing electronic board
525D005B	6 x 0,22mm ² CEI 20-22 SMART unit blue electrical cable, price per meter
525D011B	8x0,35mmq PTU electrical cable, price per meter
525D013B	6 x 0,22mm ² CEI 20-22 SMART unit grey electrical cable, price per meter
540Z003B	PTU transmitters IP67 8-pin female connector to be wired
540Z004B	PTU transmitters IP67 female connector + 5m 8 wires cable
540Z005B	PTU transmitters IP67 female connector + 10m 8 wires cable
540Z008B	PTU transmitters IP67 female connector + 15m 8 wires cable
540Z010B	PTU transmitters IP67 female connector + 20m 8 wires cable
545A047N	GWPLAST75-GWT 650°C IP56 connection box 120x80x50 with cable glands and terminal strips
546A070N	Transparent cap for PC housing "F" (METER)
620A004T	2" PP SMART/METER unit ring nuts couple
694A002A	RS485/RS232 DB9 converter module to plug to PC COM for the SMARTCOST link
694A003A	RS485/RS232 DB9 converter module to plug to PC COM with external power supply
694A004A	RS485/USB converter module to plug to PC USB for the SMARTCOST link
835A006A	PTU Lateral 316SS fixing-bracket with 0,7-1,1m adj. arm 2"BSP (see drg.)
835A007A	h=0,6m vertical SS316 pedestal
835A008A	h=1,7m vertical SS316 pedestal (see drg.)
835A009A	316SS swing sun protector plate (see drg.)
835A010A	PTU transmitters Wall mounting Vessel/channel lateral 316SS fixing-bracket
835A011A	METER lateral 316SS fixing-bracket with 0,7-1,1m adj. arm 2"BSP
835A012A	METER transmitters Wall mounting Vessel/channel lateral 316SS fixing-bracket






RPL51

Radar level transmitter

Micro-waves pulse group C
 For liquids measurement also with strong erosive products
 Max. distance: 30m
 Accuracy: $\pm 10\text{mm}$
 Process pressure: $-1,0 \div 3\text{bar}$
 Conic antenna length: 270mm

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Process temperature	
A	Mono-pole / PP / $-20 \div +100^{\circ}\text{C}$
B	Mono-pole / PTFE / $-40 \div +120^{\circ}\text{C}$
Antenna extension (blind zone H)	
A	68mm (standard)
B	118mm
C	168mm
D	218mm
E	268mm
F	318mm
Process connection / Material	
GP	Thread G1" $\frac{1}{2}$ A / PVDF (PN3)
ZZ	Special
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART(4-wire); 24Vdc
D	4÷20mA HART(4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparent cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No



H
50
100
150
200
250
300






RPL52

Radar level transmitter

Micro-waves pulse group C
 For liquids measurement also with strong erosive products
 Max. distance: 30m
 Accuracy: $\pm 10\text{mm}$
 Process pressure: $-1,0 \div 16\text{bar}$
 Conic antenna extension: 270mm

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Process temperature	
B	Mono-pole / PTFE / $-40 \div +150^{\circ}\text{C}$
Antenna extension (blind zone H)	
A	68mm
B	118mm
C	168mm
D	218mm
E	268mm
F	318mm
Process connection / Material	
FC	PTFE protected flange DN50 PN16 / SS316L
FD	PTFE protected flange DN80 PN16 / SS316L
FE	PTFE protected flange DN100 PN16 / SS316L
FK	PTFE protected flange DN150 PN16 / SS316L
ZZ	Special
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4-wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparent cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No





H
50
100
150
200
250
300

	K	b	C
DN50	Ø125	Ø165	Ø16x4
DN80	Ø160	Ø200	Ø16x8
DN100	Ø180	Ø220	Ø16x8
DN150	Ø240	Ø285	Ø20x8




RPL53

Radar level transmitter

Micro-waves pulse group C
For liquids and bulk-solids storage and process applications
Max. distance: 30m
Accuracy: $\pm 10\text{mm}$
Process pressure: $-1,0 \div 40\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material	
C	Horn Ø50mm / SS316L (only for standpipe applications)
D	Horn Ø80mm / SS316L (only for standpipe applications)
E	Horn Ø100mm / SS316L
F	Horn Ø140mm / SS316L
Antenna extension	
A	None
B	200mm
C	500mm
Process connection / Material	
FA	DN50 PN16 flange / SS316L
FB	DN80 PN16 flange / SS316L
FC	DN100 PN16 flange / SS316L
FD	DN150 PN16 flange / SS316L
FE	DN200 PN16 flange / SS316L
FH	DN250 PN16 flange / SS316L
ZZ	Special
Seal / Process temperature	
2	Viton / $-40 \div 130^\circ\text{C}$
3	Kalrez / $-20 \div 130^\circ\text{C}$
4	Viton / $-40 \div 200^\circ\text{C}$ with radiator fins
5	Kalrez / $-20 \div 200^\circ\text{C}$ with radiator fins
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4 wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparente cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No



	a	K	b	C	H	H1
DN50		Ø125	Ø165	Ø16x4		123
DN80	Ø75	Ø160	Ø200	Ø16x8	60	123
DN100	Ø96	Ø180	Ø220	Ø16x8	120	123
DN150	Ø146	Ø240	Ø285	Ø20x8	205	123
DN200	Ø197	Ø295	Ø340	Ø20x12	296	123
DN250	Ø244	Ø355	Ø405	Ø24x12	380	123





RPL54

Radar level transmitter

Micro-waves pulse group C
 For liquids and bulk-solids storage and process applications
 Max. distance: 70m
 Accuracy: $\pm 20\text{mm}$
 Process pressure: $-1 \div 40\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material	
F	Horn Ø150mm / SS316L
G	Horn Ø200mm / SS316L
H	Horn Ø250mm / SS316L
Antenna extension	
A	None
B	200mm
C	300mm
D	400mm
Process connection / Material	
FB	DN150 PN16 flange / SS316L
FC	DN200 PN16 flange / SS316L
FD	DN250 PN16 flange / SS316L
ZZ	Special
Seal / Process temperature	
2	Viton / $-40 \div 130^\circ\text{C}$
3	Kalrez / $-20 \div 130^\circ\text{C}$
4	Viton / $-40 \div 200^\circ\text{C}$ with radiator fins
5	Kalrez / $-20 \div 200^\circ\text{C}$ with radiator fins
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparent cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No



	a	K	b	C	H	H1
DN150	Ø146	Ø240	Ø285	Ø20x8	205	123
DN200	Ø197	Ø295	Ø340	Ø20x12	296	123
DN250	Ø244	Ø355	Ø405	Ø24x12	380	123






RPL55

Radar level transmitter

Micro-waves pulse 26GHz group K
For storage or process applications
Max distance: 10m
Accuracy: $\pm 5\text{mm}$
Process pressure: $-1 \div 3\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Process temperature	
B	Mono-pole / PTFE / $-40^{\circ} \div +120^{\circ}\text{C}$
Process connection / Material	
GP	Thread G 1"½ / PTFE
ZZ	Special
Non sensitive part (for nozzle mounting)	
A	100 mm
B	200 mm
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4-wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparent cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No







RPL56

Radars level transmitter

Micro-waves pulse 26GHz group K
For storage or process applications
Max distance: 30m
Accuracy: $\pm 3\text{mm}$
Process pressure: $-1 \div 40\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material	
B	Horn antenna Ø48mm / SS316L
C	Horn antenna Ø78mm / SS316L
H	Horn antenna Ø98mm / SS316L
K	Horn antenna Ø98mm with aiming device / PP with PTFE cap
Process connection / Material	
GC	Thread G 1" ½ with dissipator / SS316L (-60 ~ 250°C)
GD	Thread G 1" ½ with dissipator and flange / SS316L (-60 ~ 400°C); pressure 40MPa
GP	Thread G 1" ½ / SS316L
ZZ	Special
Additional flange (DN / Material)	
FA	DN50 / PP
FB	DN50 / PTFE
FC	DN50 / SS316
GA	DN80 / PP
GB	DN80 / PTFE
GC	DN80 / SS316
HA	DN100 / PP
HB	DN100 / PTFE
HC	DN100 / SS316
OO	None
ZZ	Special
Seal / Process temperature	
2	Viton / $-40 \div 130^\circ\text{C}$
3	Kalrez / $-60 \div 250^\circ\text{C}$
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4-wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparent cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No



	c	H
2"	$\Phi 48$	120
3"	$\Phi 75$	200
4"	$\Phi 95$	300



RPL58

Radar level transmitter

Micro-waves pulse 26GHz group K
For storage or process applications
Max distance: 70m
Accuracy: $\pm 15\text{mm}$
Process pressure: $-1 \div 40\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard

Antenna shape / Material	
B	Horn antenna Ø48mm / SS316L
C	Horn antenna Ø78mm / SS316L
H	Horn antenna Ø98mm / SS316L
K	Horn antenna Ø98mm / PP with PTFE cap
M	Horn antenna Ø98mm / SST316L with PTFE cap
P	Horn antenna Ø123mm / SST316L with PTFE cap
Q	Parabolic horn Ø198mm / SST316L
R	Parabolic horn Ø246mm / SST316L



Process connection / Material	
GC	Thread G 1" ½ with dissipator / SS316L
GE	Thread G 1" ½ / SS316L with insufflate aria
GP	Thread G 1" ½ / SS316L
ZZ	Special

Additional flange (DN / Material)	
FA	DN50 / PP
FB	DN50 / PTFE
FC	DN50 / SS316
GA	DN80 / PP
GB	DN80 / PTFE
GC	DN80 / SS316
HA	DN100 / PP
HB	DN100 / PTFE
HC	DN100 / SS316
HE	Aiming device DN100 / SS316
JA	DN150 / PP
JB	DN150 / PTFE
JC	DN150 / SS316
JE	Aiming device DN150 / SS316
KA	DN200 / PP
KB	DN200 / PTFE
KC	DN200 / SS316
KE	Aiming device DN200 / SS316
LA	DN250 / PP
LB	DN250 / PTFE
LC	DN250 / SS316
LE	Aiming device DN250 / SS316
OO	None
ZZ	Special




Seal / Process temperature	
2	Viton / $-40 \div 130^{\circ}\text{C}$
3	Kalrez / $-60 \div 250^{\circ}\text{C}$





Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Housing protection / Antenna protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67 / IP67
U	Aluminum with transparent cap / IP67 / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No



C	H
Ø 48	120
Ø 78	200
Ø 98	300



C	H1
Ø 48	120
Ø 78	200
Ø 98	300



	a	b	H	d
DN50	165	122,8	11,5	4 x Ø19
DN80	205	156,2	11,5	8 x Ø16
DN100	220	182,5	11,5	8 x Ø16
DN150	285	240	11,5	8 x Ø20
DN200	340	295	11,5	12 x Ø20
DN250	355	182,5	11,5	12 x Ø24




RWL51

Guided microwave radar level transmitter

Microwaves pulse TDR
 For liquids and bulk solids measurement
 Max. length: rod 3m , rope 30m (Ø4mm or Ø6mm according to the application)
 Accuracy: ±10mm
 Process pressure: -1÷40 bar

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Sealing	
A	Rope Ø4mm (up to 5m) or Rope Ø 6mm (over 5m) / SS316L / PTFE
B	Rod Ø10mm / SS316L / PTFE
X	None
Process connection / Material	
GP	Thread G1 ½" A / SS316L
KP	Thread G2" A / SS316L
ZZ	Special
Seal / Process temperature	
A	Viton / -30÷130°C
B	Kalrez / -40÷150°C
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4wire); 24Vdc
D	4÷20mA HART (4wire); 230Vac
Housing / Protection	
D	Aluminum 2 chambers (for 4-wire versions) / IP67
U	Aluminum with transparent cap / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No
L= length, price each 100mm	
A	Rope Ø4/6mm / SS316L (max 25m)
B	Rod Ø10mm / SS316L (max 3m)
C	Rod Ø10mm / SS304 (max 3m)






RWL52

Guided microwave radar level transmitter

Microwaves pulse TDR
For liquids and bulk solids measurement
Max. length: 3m
Accuracy: $\pm 10\text{mm}$
Process pressure: $-1 \div 40\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Sealing	
A	Rod $\varnothing 10\text{mm}$ / SS316L / PTFE
Process connection / Material	
FA	Flange DN50 PN16 / SS316L
FB	Flange DN80 PN16 / SS316L
FC	Flange DN100 PN16 / SS316L
FD	Flange DN150 PN16 / SS316L
ZZ	Special
Seal / Process temperature	
A	Viton / $-30 \div 130^\circ\text{C}$
Electronic preamplifier	
B	$4 \div 20\text{mA}$ HART (2-wire); 24Vdc
C	$4 \div 20\text{mA}$ HART (4-wire); 24Vdc
D	$4 \div 20\text{mA}$ HART (4-wire); 230Vac
Housing / Protection	
D	Aluminum with 2 chambers (for 4-wire versions) / IP67
U	Aluminum with transparent cap / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No
L= length, price each 100mm	
A	Rod $\varnothing 10\text{mm}$ / SS316L (max 3m)






RWL53

Guided microwave radar level transmitter

Microwaves pulse TDR
For small dielectric constant liquids (oils, distilled water, others)
Max. length: 3m
Accuracy: $\pm 10\text{mm}$
Process pressure: $-1 \div 40\text{bar}$

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Sealing	
A	Coaxial $\varnothing 28\text{mm}$ / SS316L / PTFE
Process connection / Material	
GP	Thread G1" $\frac{1}{2}$ A / SS316L
KP	Thread G2" A / SS316L
ZZ	Special
Seal / Process temperature	
A	Viton / $-30 \div 130^\circ\text{C}$
B	Kalrez / $-40 \div 150^\circ\text{C}$
Electronic preamplifier	
B	4÷20mA HART (2-wire); 24Vdc
C	4÷20mA HART (4wire); 24Vdc
D	4÷20mA HART (4-wire); 230Vac
Housing / Protection	
D	Aluminum with 2 chambers (for 4-wire versions) / IP67
U	Aluminum with transparent cap / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No
L= length, price each 100mm	
A	Coaxial $\varnothing 28\text{mm}$ / SS316L (max 3m)





RWL54



Guided microwave radar level transmitter

Microwaves pulse TDR
 For liquids with high process temperature/pressure
 Max. length: 3m rod - 30m rope
 Accuracy: $\pm 10\text{mm}$
 Process pressure: $-1 \div 40\text{bar}$
 Process temperature: max 200°C

Version	
I	Intrinsically safe CENELEC EExia IIC T6
P	Standard
Antenna shape / Material / Sealing	
A	Rope $\varnothing 4\text{mm}$ (up to 5m) or Rope $\varnothing 6\text{mm}$ (over 5m) / SS316L / PTFE
B	Rod $\varnothing 10\text{mm}$ / SS316L / PTFE
Process connection / Material	
GP	Thread G1" $\frac{1}{2}$ A / SS316L
KP	Thread G2" A / SS316L
ZZ	Special
Seal	
A	Viton
B	Kalrez
Electronic preamplifier	
B	$4 \div 20\text{mA}$ HART (2-wire); 24Vdc
C	$4 \div 20\text{mA}$ HART (4-wire); 24Vdc
D	$4 \div 20\text{mA}$ HART (4-wire); 230Vac
Housing / Protection	
D	Aluminum with 2 chambers (for 4-wire versions) / IP67
U	Aluminum with transparent cap / IP67
Z	Special
Cable entry	
M	M20x1,5
Keyboard/display programming module VL601	
A	Yes
X	No
L= Electrode length, price each 100mm	
A	Rope $\varnothing 4/6\text{mm}$ / SS316L (max 30m)
B	Rod $\varnothing 10\text{mm}$ / SS316L (max 3m)
C	Rod $\varnothing 10\text{mm}$ / SS304 (max 3m)



Radars



Capacitive



CLT4

Capacitive rod probe for liquids

Suitable for level measurement in conductive and non-conductive liquids
Installation in the top of metallic tanks; 3m max.

Version	
A	Without insert-preamplifier (only capacitive electrode + head connection)
B	Compact
C	Compact Intrinsic Safe, ATEX II 1 GD EExia II C T4..T6 IP65 T85°C certified (select TC30 insert only)
D	Spacer-cooling-fins compact in carbon-steel
F	Spacer-cooling-fins compact in stainless-steel
H	Separate, IP66 preampl.head + Electrode and DIN A Al head + 1,5m coaxcable
L	Spacer-cooling-fins compact in carbon-s., ATEX II 1 GD EExia II C T4..T6 IP65 T85°C cert. (select TC30 insert only)
M	Spacer-cooling-fins compact in S.S., ATEX II 1 GD EExia II C T4..T6 IP65 T85°C cert. (select TC30 insert only)
N	Separate, IP66 preampl.head with Al fixing base + 2m coaxcable
Z	Special
Electronic preamplifier	
00	None
22	TC22, 4÷20mA, 2 push buttons for calibration, 24Vdc
23	TC23, 4÷20mA, 2 push buttons for calibration, 24Vac
24	TC24, 4÷20mA, 2 push buttons for calibration, 115Vac
25	TC25, 4÷20mA, 2 push-buttons calibration, 230Vac
26	TC26, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vdc
27	TC27, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vac
28	TC28, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 115Vac
29	TC29, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 230Vac
30	TC30, 4÷20mA 2-wire, 2 push-buttons calibration, 24Vdc
99	Special
Housing	
B	IP66 loaded PC ; white polycarbonate cap
C	IP65 aluminium varnished
D	IP65 double cover PBT
G	IP66 aluminum varnished with 2 cable-glands
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special
Process connection	
01	G1" (G 1 A) / Carbon-steel
02	G1" (G 1 A) / Stainless-steel SS316
03	1" NPT / Carbon-steel
04	1" NPT / Stainless-steel SS316
11	G1½" (G 1 ½ A) / Carbon-steel
12	G1½" (G 1 ½ A) / Stainless-steel SS316
18	G1½" (G 1 ½ A) / PVC
19	G1½" (G 1 ½ A) / PTFE
20	Sanitary DN 25 DIN 11851, SS304L
21	Sanitary DN 40 DIN 11851, SS304L
22	Sanitary DN 50 DIN 11851, SS304L
40	Flange DN 40 PN 6 UNI 1092-1 material PVC
41	Flange DN 40 PN 6 UNI6991/71material PTFE
42	Flange DN 40 PN16 material Carbon-steel
45	Flange DN 50 PN6 UNI 1092-1 material PVC
46	Flange DN 80 PN6 UNI 1092-1 material PVC
47	Flange DN 100 PN6 UNI 1092-1 material PVC
50	Flange DN 40 PN16 material SS304
51	Flange DN 40 PN16 material SS316



52	Flange DN 50 PN16 DIN 2527 form B (without gasket) SS316
53	Flange DN 80 PN16 DIN 2527 form B (without gasket) SS316
54	Flange DN 100 PN16 DIN 2527 form B (without gasket) SS316
60	Flange ANSI RF 2" 150 psi SS316
61	Flange ANSI RF 3" 150 psi SS316
62	Flange ANSI RF 4" 150 psi SS316
71	CLAMP 1" SS316
73	CLAMP 1 1/2" SS316
75	CLAMP 2" SS316
83	G½" (G ½ A) / Carbon-steel
84	G½" (G ½ A) / Stainless-steel SS316
99	Special

Electrode type and insulation


B	PTFE partially insulated SS316 rod
D	PVC totally insulated SS316 rod
H	PTFE totally insulated SS316 rod
M	PTFE partially insulated SS316 rod + Carbon steel concentric reference electrode
N	PVC insulated rod + Carbon steel concentric reference electrode
P	PTFE insulated rod + Carbon steel concentric reference electrode
Q	PTFE partially insulated SS316 rod + AISI316 concentric reference electrode
R	PVC insulated rod + SS316 concentric reference electrode
S	PTFE insulated rod + SS316 concentric reference electrode
Z	Special

L= Electrode length, price each 100mm

40	PTFE partially insulated SS316 rod
42	PVC totally insulated SS316 rod
46	PTFE totally insulated SS316 rod
50	PTFE partially insulated SS316 rod + Carbon steel concentric reference electrode
51	PVC insulated rod + Carbon steel concentric reference electrode
52	PTFE insulated rod + Carbon steel concentric reference electrode
53	PTFE partially insulated SS316 rod + SS316 concentric reference electrode
54	PVC insulated rod + SS316 concentric reference electrode
55	PTFE insulated rod + SS316 concentric reference electrode
99	Special

L1 = non sensitive part (rod), material and price each 10cm

A	Standard
B	Carbon-steel
C	SS316
Z	Special



Capacitive



CLT5

Capacitive double-rods probe for liquids


Continuous capacitive level measurement
Installation in the top of non-metallic tanks; 3m max.

Version	
A	Without insert-preamplifier (only capacitive electrode + head connection)
B	Compact
H	Separate, IP66 preampl. head + Electrode and DIN A AI head + 1,5m coax cable
Z	Special
Electronic preamplifier	
00	None
22	TC22, 4÷20mA, 2 push buttons for calibration, 24Vdc
23	TC23, 4÷20mA, 2 push buttons for calibration, 24Vac
24	TC24, 4÷20mA, 2 push buttons for calibration, 115Vac
25	TC25, 4÷20mA, 2 push buttons for calibration, 230Vac
26	TC26, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vdc
27	TC27, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vac
28	TC28, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 115Vac
29	TC29, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 230Vac
30	TC30, 2wires, 2 push buttons for calibration, 24Vdc
99	Special
Housing	
B	IP66 loaded PC ; white polycarbonate cap
D	IP65 Double cover PBT
Z	Special
Process connection	
18	G1"½ (G 1 ½ A) / PVC
19	G1"½ (G 1 ½ A) / PTFE
40	Flange DN40 PN6 UNI 1092-1, material PVC
41	Flange DN40 PN6 UNI 1092-1, material PTFE
45	Flange DN50 PN6 UNI 1092-1, material PVC
46	Flange DN80 PN6 UNI 1092-1, material PVC
47	Flange DN100 PN6 UNI 1092-1, material PVC
99	Special
Electrode type and insulation	
B	PTFE partially insulated SS316
D	PVC totally insulated
H	PTFE totally insulated
Z	Special
L= insertion length (electrodes couple), price each 100mm	
40	PTFE partially insulated SS316 rod
42	PVC totally insulated (with spreader each meter)
46	PTFE totally insulated (with spreader each meter)
99	Special



Capacitive

41



Capacitive



CLT7

Capacitive rope probe for granulates and powders

Continuous capacitive level measurement
Installation on the top of metallic tanks

Version	
A	Without insert-preamplifier (only capacitive electrode + head connection)
B	Compact version
C	Compact Intrinsic Safe, ATEX II 1 GD EExia II C T4..T6 IP65 T85°C certified (select TC30 insert only)
H	Separate, IP66 preampl.head + Electrode and DIN A Al head + 1,5m coaxcable
N	Separate, IP66 preampl.head with Al fixing base + 1,7m coaxcable
Z	Special
Electronic preamplifier	
00	None
22	TC22, 4÷20mA, 2 push buttons for calibration, 24Vdc
23	TC23, 4÷20mA, 2 push buttons for calibration, 24Vac
24	TC24, 4÷20mA, 2 push buttons for calibration, 115Vac
25	TC25, 4÷20mA, 2 push buttons for calibration,, 230Vac
26	TC26, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vdc
27	TC27, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vac
28	TC28, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 115Vac
29	TC29, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 230Vac
30	TC30, 2wires, 2 push buttons for calibration, 24Vdc
99	Special
Housing	
B	IP66 loaded PC; white polycarbonate cap
C	IP65 aluminium varnished
D	IP65 Double cover PBT
G	IP66 aluminium varnished with 2 cable-glands
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special
Process connection	
11	G1"½ (G 1 ½ A) / Carbon-steel
12	G1"½ (G 1 ½ A) / SS316
42	Flange DN40 PN16 material Carbon-steel
50	Flange DN 40 PN16 material SS304
51	Flange DN 40 PN16 material SS316
52	Flange DN 50 PN16 DIN 2527 form B (without gasket) SS316
53	Flange DN 80 PN16 DIN 2527 form B (without gasket) SS316
54	Flange DN 100 PN16 DIN 2527 form B (without gasket) SS316
60	Flange ANSI RF 2" 150 psi SS316
61	Flange ANSI RF 3" 150 psi SS316
62	Flange ANSI RF 4" 150 psi SS316
99	Special




Capacitive

43

Electrode type and insulation	
L	Ø8mm carbon steel, counterweight in carbon steel
M	Ø8mm carbon steel, counterweight in SS316
N	Ø8mm carbon steel PE coated, counterweight in carbon steel
P	Ø8mm carbon steel PE coated, counterweight in SS316
Z	Special

L= Electrode length, price each meter	
73	Ø8mm carbon steel
74	Ø8mm carbon steel PE coated
99	Special

L1 = non sensitive part (rod), material and price each 10cm	
A	Standard
B	Carbon-steel
C	SS316
Z	Special



Capacitive



CLT8

Capacitive rope probe for liquids

Continuous capacitive level measurement
Suitable for conductive and not conductive liquids, paste
Installation on the top of metallic tanks
IP66 mechanical protection

Version	
A	Without insert-preamplifier (only capacitive electrode + head connection)
B	Compact
C	Compact Intrinsic Safe, ATEX II 1 GD EExia II C T4..T6 IP65 T85°C certified (select TC30 insert only)
D	Spacer-cooling-fins compact in carbon-steel
F	Spacer-cooling-fins compact in stainless-steel
H	Separate, IP66 preampl.head + Electrode and DIN-A Al head + 1,5m coaxcable
L	Spacer-cooling-fins compact in carbon-s., ATEX II 1 GD EExia II C T4..T6 IP65 T85°C cert. (select TC30 insert only)
M	Spacer-cooling-fins compact in S.S., ATEX II 1 GD EExia II C T4..T6 IP65 T85°C cert. (select TC30 insert only)
N	Separate, IP66 preampl.head with Al fixing base + 1,7m coaxcable
Z	Special
Electronic preamplifier	
00	None
22	TC22, 4÷20mA, 2 push buttons for calibration, 24Vdc
23	TC23, 4÷20mA, 2 push buttons for calibration, 24Vac.
24	TC24, 4÷20mA, 2 push buttons for calibration, 115Vac.
25	TC25, 4÷20mA, 2 push buttons for calibration, 230Vac.
26	TC26, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vdc
27	TC27, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 24Vac
28	TC28, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 115Vac
29	TC29, 4÷20mA, 2 push-buttons calibration, 1relay, RS485, 230Vac
30	TC30, 2wires, 2 push buttons for calibration, 24Vdc
99	Special
Housing	
B	IP66 loaded PC; white polycarbonate cap
C	IP65 aluminium varnished
D	Double cover PBT IP65
G	IP66 aluminium varnished with 2 cable-glands
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special
Process connection	
02	G1" (G 1 A) / Stainless-steel SS316
04	1" NPT / Stainless-steel SS 316
11	G1½" (G 1 ½ A) / Carbon-steel
12	G1½" (G 1 ½ A) / Stainless-steel SS316
18	G1½" (G 1 ½ A) / PVC
19	G1½" (G 1 ½ A) / PTFE
20	Sanitary DN 25 DIN 11851, SS 304L
21	Sanitary DN 40 DIN 11851, SS 304L
22	Sanitary DN 50 DIN 11851, SS 304L
42	Flange DN 40 PN16 material Carbon-steel
50	Flange DN 40 PN16 material SS 304
51	Flange DN 40 - PN16 material SS 316
52	Flange DN 50 - PN16 DIN 2527 form B (without gasket) SS 316
53	Flange DN 80 PN16 DIN 2527 form B (without gasket) SS 316
54	Flange DN 100 PN16 DIN 2527 form B (without gasket) SS 316



Capacitive

45

60	Flange ANSI RF 2" 150 psi SS 316
61	Flange ANSI RF 3" 150 psi SS 316
62	Flange ANSI RF 4" 150 psi SS 316
71	CLAMP 1" SS 316
73	CLAMP 1 1/2" SS 316
75	CLAMP 2" SS 316
99	Special

Electrode type and insulation


B	Ø2,5mm PVC insulated, counterweight in SS316
C	Ø2,5mm PTFE insulated, counterweight in SS316
L	Ø2,5mm PVC insulated, counterweight in PVC
M	Ø2,5mm PTFE insulated, counterweight in PTFE
Z	Special

L= Electrode length, price each meter

81	Ø2,5mm PVC insulated
82	Ø2,5mm PTFE insulated
99	Special

L1 = non sensitive part (rod), material and price each 10cm

A	Standard
C	SS316
Z	Special



Purge



PVI

Air purge level transmitter unit with 4 threshold relays

Air purge: connection to a 20PSI air instrumentation, (137,895 kPa)

Analog output: 0÷10Vdc min 3kohm, and 4÷20mA max 500ohm

Mechanical protection: IP10






Working temperature -10, +50°C,

Version	
0	Level transmitter, IP10 DIN-rail mounting
1	Level transmitter + 4 relays SPDT, IP10 DIN-rail mounting
9	Special

Power supply	
A	24Vac 50÷60Hz
B	115Vac 50÷60Hz
C	230Vac 50÷60Hz

Measure range	
1	0÷1000mm H ₂ O, (0÷9,80665kPa)
2	0÷5000mm H ₂ O, (0÷4,903325kPa)
5	For differential pressure 0÷100mm H ₂ O, (0÷0,980665kPa)
9	Special

Accessories	
A	None
Z	Special





Purge

PTS

Air purge level transmitter unit with 1/2 threshold relays



Air purge; connection to a 20PSI air instrumentation, (137,895 kPa)

Undecal socket mounting into DIN-rail

Zero and Span frontal trimmers adjustment n

Working temperature -10, +50°C

Version	
A	IP20, n.1 threshold relay
B	IP20, n.2 threshold relays
Z	Special
Power supply	
0	24Vac 50/60 Hz
1	115Vac 50/60 Hz
2	230Vac 50/60 Hz
4	24Vdc
9	Special
Output	
A	4÷20mA
B	0÷10V
Z	Special
Measure range	
2	0÷1000mm H ₂ O, (0÷9,80665kPa)
4	0÷5000mm H ₂ O, (0÷4,903325kPa)
9	Special max 20.000mm H ₂ O, (0÷196,133kPa)
Accessories	
A	None
B	Socket and fixing spring
Z	Special




Visualization and control

LC2 2 relays switch and power control unit for transmitters

Trim-adjustable 4÷20mA input / 2 relays output
Suitable to be connected to "general purpose" transmitters (TC, PTU, SMART)
Transmitter supply output 24Vdc - max 200mA
Frontal trimmers adjustment for switch points calibration and time delay 0÷12s
Power supply: 85÷255 Vac - Working temperature: -10 ÷ +50°C
Undecal socket mounting, IP20

Version	
A	Standard
Z	Special





VL501 4÷20mA loop powered digital display

3 1/2digit LCD
Fine calibration with dip-switches
Zero and Span setting with internal simulator
Panel mounting std 48x96mm, IP40 frontal

Accessories	
A	None
M	Frontal window IP54
Z	Special



VL501



VLW501 4÷20mA IP66 loop powered digital display

Base	
VLW501	3 1/2digit LCD Fine calibration with dip-switches Zero and Span setting with internal simulator Wall mounting, IP66



Visualization and control

SLA2X

Display and control unit

5 ½ digit led display, suitable to be connected to analogic transmitters
 Power supply output: 24Vdc; max.40mA
 4 frontal push-buttons for calibration; level auto-calibration is available
 Working temperature -10, +50°C, Front panel mounting 48 x 96
 IP40 frontal mechanical protection

Power supply	
0	115Vac 50÷60Hz
1	230Vac 50÷60Hz
2	24Vac 50÷60Hz
3	24Vdc
Relay	
0	None
2	2 Relays
4	4 Relays
Output	
A	None
D	RS485 MODBUS
R	RS232
T	4÷20mA / 0÷10V
Linearization	
A	None
L	With up to 20 segments programmable
Input galvanic insulation	
A	None
D	Input galvanic insulation (only with 24Vdc power supply)
Accessories	
A	None
M	Frontal windows IP54
N	Enclosure for external mounting IP66
Z	Special






Visualization and control

CVI

4 relays switch and power control unit for transmitters

- Suitable to be connected to general purpose transmitters (TC, PTU, SMART)
- Maximum current consumption 150mA
- Analogic output 4÷20mA and 0÷10V
- Frontal trimmers (4) adjustment for switch points calibration
- Panel mounting (DIN rail) IP10
- Working temperature -20 ÷ +60°C,

Input	
A	0/4÷20mA
Z	Special
Power supply	
1	24Vac 50÷60Hz
2	115Vac 50÷60Hz
3	230Vac 50÷60Hz






Visualization and control

A2S

Control unit for 4÷20mA 2 relays transmitters

Suitable to be connected to 4÷20mA analogic transmitters
2 SPDT 3A 250Vac relays, trimmer adjustable set points
IP20 mechanical protection; Undecal plug-in male-socket

Input	
A	4÷20mA
B	0÷10V
Z	Special
Power supply	
0	24Vac 50-60 Hz
1	115Vac 50-60 Hz
2	230Vac 50-60 Hz
4	24Vdc
Accessories	
A	None
B	Socket and fixing spring
Z	Special



Visualization and control

CLS2

Standard rod level switch

ON/OFF capacitive level control
Top and lateral side metallic tank-installation
Standard length: 250mm


Version	
A	Without preamplifier insert (only capacitive electrode)
B	Compact
E	Compact, dust ATEX Zone 20/21 certificated (TL41 insert); to be used with " G" housing
F	Compact with SS316 dissipator (use same of process conn.)
Z	Special
Electronic preamplifier	
00	None
33	TL31R ON-OFF, supply 24Vdc, Relay output SPDT
34	TL31R ON-OFF, supply 24Vac, Relay output SPDT
35	TL31R ON-OFF, supply 115Vac, Relay output SPDT
36	TL31R ON-OFF, supply 230Vac, Relay output SPDT
41	TL41 ON-OFF, supply 20÷30Vdc/Vac 50Hz, Relay output SPDT
43	TL41 ON-OFF, supply 85÷250Vac 50Hz, Relay output SPDT
99	Special
Housing	
B	IP66 PC (loaded-polycarbonate)
D	IP65 Double cover PBT
G	IP66 aluminum varnished (necessary for ATEX version)
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special
Process connection	
01	G1" (G 1 A) / Carbon-steel
02	G1" (G 1 A) / SS316
11	G1"½ (G 1 ½ A) / Carbon steel
12	G1"½ (G 1 ½ A) / SS316
92	G ¾" (G ¾ A) / SS316
99	Special
Electrode type and insulation	
B	Partially PVC insulated Ø15mm Carbon-steel rod
C	Ø15mm Carbon-steel rod with extended PVC insulation
D	Partially PTFE insulated Ø15mm Carbon-steel rod
H	Partially PVC insulated Ø15mm SS316 rod
I	Ø15mm SS316 rod with extended PVC insulation
L	Partially PTFE insulated Ø15mm SS316 rod
Z	Special
M10x1,5 female thread for extension	
0	None
1	M10x1,5 female thread on top



Capacitive

53

Non sensitive part	
A	50mm standard (carbon-steel or SS316 function of the process connection)
B	100mm Carbon-steel, (same of material select in process-connection)
Extension type	
000	None
400	Ø10mm SS316 rod
700	Ø6mm Carbon-steel rope + carbon-steel counterweight (type 50) Warning! For length over 3m, extra price of 30,00 EUR
Extension length	
A	None
B	Rigid rod, price each 10cm
C	Carbon-steel rope Ø6mm, price each m.



Capacitive



CLS4

Rod level switch



ON/OFF capacitive level control
Suitable for conductive and non-conductive liquids
Top and lateral side metallic tank-installation

Version	
A	Without preamplifier (only capacitive electrode)
B	Compact
D	Compact with carbon-steel dissipator between head and connection
E	Compact, Zone 20/21 ATEX certificated (TL41 insert only); to be used with "G" housing
F	Compact, with SS316 dissipator between head and connection
H	Separate insert, DIN A aluminum electrode head, 1,5m coax cable (PTFE/SIL.)
N	Compact, with carbon-steel dissipator, Zone 20/21 ATEX cert. (TL41 insert only); to be used with "G" housing
P	Compact, with SS316 dissipator, Zone 20/21 ATEX cert. (TL41 insert only); to be used with "G" housing
Z	Special

Electronic preamplifier	
00	None
33	TL31R ON-OFF local sensibility calibration supply 24Vdc, Relay output SPDT
34	TL31R ON-OFF local sensibility calibration supply 24Vac, Relay output SPDT
35	TL31R ON-OFF local sensibility calibration supply 115Vac, Relay output SPDT
36	TL31R ON-OFF local sensibility calibration supply 230Vac, Relay output SPDT
41	TL41 ON-OFF, supply 20÷30Vdc/Vac 50Hz, Relay output SPDT
43	TL41 ON-OFF, supply 85÷250Vac 50Hz, Relay output SPDT
73	TC7.3R local calibration, 24Vdc, 3 relays out for 3 adjustable set-points
99	Special

Housing	
B	IP66 PC polycarbonate loaded
C	IP65 aluminum varnished
D	IP65 double cover PBT
G	IP66 aluminum varnished (necessary for ATEX versions)
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special

Process connection	
01	G1" (G 1 A) / Carbon-steel
02	G1" (G 1 A) / SS316
03	1" NPT-M / Carbon-steel
04	1" NPT-M / SS316
11	G1½" (G 1 ½ A) / Carbon-steel
12	G1½" (G 1 ½ A) / SS316





18	G1"½ (G 1 ½ A) / PVC
19	G1"½ (G 1 ½ A) / PTFE
20	Sanitary DN25 DIN 11851, SS304L
21	Sanitary DN40 DIN 11851, SS304L
22	Sanitary DN50 DIN 11851, SS304L
40	Flange DN40 PN6 UNI 1092-1, PVC
41	Flange DN40 PN 6 UNI6991/71, PTFE
42	Flange DN40 PN16, Carbon-steel
45	Flange DN50 PN6 UNI 1092-1, PVC
46	Flange DN80 PN6 UNI 1092-1, PVC
47	Flange DN100 PN6 UNI 1092-1, PVC
50	Flange DN40 PN16, SS304
51	Flange DN40 PN16, SS316
52	Flange DN50 PN16 DIN 2527 form B (without gasket), SS316
53	Flange DN80 PN16 DIN 2527 form B (without gasket), SS316
54	Flange DN100 PN16 DIN 2527 form B (without gasket), SS316
60	Flange ANSI RF 2" 150 psi, SS316
61	Flange ANSI RF 3" 150 psi, SS316
62	Flange ANSI RF 4" 150 psi, SS316
71	CLAMP 1" SS316
73	CLAMP 1 1/2" SS316
75	CLAMP 2" SS316
99	Special

Electrode type and insulation

B	PTFE partially insulated SS316 rod
C	SS316 rod with extended PVC insulation
D	PVC totally insulated SS316 rod
G	SS316 rod with extended PTFE insulation
H	SS316 rod PTFE totally insulated
M	PTFE partially insulated SS316 rod + Carbon steel concentric reference electrode
N	PVC totally insulated SS316 rod + Carbon steel concentric reference electrode
P	PTFE totally insulated SS316 rod + Carbon steel concentric reference electrode
Q	PTFE partially insulated SS316 rod + SS316 concentric reference electrode
R	PVC totally insulated SS316 rod + SS316 concentric reference electrode
S	PTFE totally insulated SS316 rod + SS316 concentric reference electrode
Z	Special

L= Electrode length, price each 100mm

40	PTFE partially insulated SS316 rod
41	SS316 rod with extended PVC insulation
42	PVC totally insulated SS316 rod
45	SS316 rod with extended PTFE insulation
46	PTFE totally insulated SS316 rod
50	PTFE partially insulated SS316 rod + Carbon steel concentric reference electrode
51	PVC totally insulated SS316 rod + Carbon steel concentric reference electrode
52	PTFE totally insulated SS316 rod + Carbon steel concentric reference electrode
53	PTFE partially insulated SS316 rod + SS316 concentric reference electrode
54	PVC totally insulated SS316 rod + SS316 concentric reference electrode
55	PTFE totally insulated SS316 rod + SS316 concentric reference electrode
99	Special

L1 = non sensitive part (rod), material and price each 10cm

A	Standard
B	Carbon-steel
C	SS316
Z	Special

Capacitive



CLS7

Rope level switch for granulates

ON/OFF capacitive level control
Suitable for bulk solid and granulates
Top side metallic tank-installation

Version	
A	Without electronic preamplifier
B	Compact
E	Compact, Zone 20/21 ATEX certified (TL41 insert only); to be used with "G" housing
H	Separate insert, DIN A aluminum electrode head, 1,5m coax cable (PTFE/SIL.)
Z	Special

Electronic preamplifier	
00	None
33	TL31R ON-OFF local sensibility calibration supply 24Vdc, Relay output SPDT
34	TL31R ON-OFF local sensibility calibration supply 24Vac, Relay output SPDT
35	TL31R ON-OFF local sensibility calibration supply 115Vac, Relay output SPDT
36	TL31R ON-OFF local sensibility calibration supply 230Vac, Relay output SPDT
41	TL41 ON-OFF, supply 20÷30Vdc/Vac 50Hz, Relay output SPDT
43	TL41 ON-OFF, supply 85÷250Vac 50Hz, Relay output SPDT
73	ON-OFF TC7.3R local calibration, 24Vdc, 3 relays out for 3 adjustable set-points
99	Special

Housing	
B	IP66 PC polycarbonate loaded
C	IP65 aluminum varnished
D	IP65 double cover PBT
G	IP66 aluminum varnished (necessary for ATEX version)
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special

Process connection	
11	G1"½ (G 1 ½ A) / Carbon-steel
42	Flange DN40 PN16, Carbon-steel
50	Flange DN40 PN16, SS304
51	Flange DN40 PN16, SS316
52	Flange DN50 PN16 DIN2527 form B (without gasket), SS316
53	Flange DN80 PN16 DIN2527 form B (without gasket), SS316
54	Flange DN100 PN16 DIN2527 form B (without gasket), SS316
60	Flange ANSI RF 2" 150psi, SS316
61	Flange ANSI RF 3" 150psi, SS316
62	Flange ANSI RF 4" 150 psi, SS316
99	Special




Capacitive

57

Electrode type and insulation	
L	Ø8mm carbon steel, counterweight in carbon steel
M	Ø8mm carbon steel, counterweight in SS316
N	Ø8mm carbon steel PE coated, counterweight in carbon steel
P	Ø8mm carbon steel PE coated, counterweight in SS316
Z	Special

L= Electrode length, price each meter	
73	Ø8mm carbon steel
74	Ø8mm carbon steel PE coated
99	Special

L1 = non sensitive part (rod), material and price each 10cm	
A	Standard
B	Carbon-steel
C	SS316
Z	Special



Capacitive



CLS8

Rope level switch for liquids

ON/OFF capacitive level control
Suitable for conductive and not conductive liquids
Top side metallic tank-installation

Version	
A	Without electronic preamplifier
B	Compact
D	Compact, with carbon steel dissipator between head and connection
E	Compact, Zone 20/21 ATEX certificated (TL41 insert only); to be used with "G" housing
F	Compact, with SS316 dissipator between head and connection
H	Separate insert, DIN A aluminum electrode head, 1,5m coax cable (PTFE/SIL.)
N	Compact, with carbon-steel dissipator, Zone 20/21 ATEX cert. (TL41 insert only); to be used with "G" housing
P	Compact, with SS316 dissipator, Zone 20/21 ATEX cert. (TL41 insert only); to be used with "G" housing
Z	Special
Electronic preamplifier	
00	None
33	TL31R ON-OFF local sensibility calibration supply 24Vdc, Relay output SPDT
34	TL31R ON-OFF local sensibility calibration supply 24Vac, Relay output SPDT
35	TL31R ON-OFF local sensibility calibration supply 115Vac, Relay output SPDT
36	TL31R ON-OFF local sensibility calibration supply 230Vac, Relay output SPDT
41	TL41 ON-OFF, supply 20÷30Vdc/Vac 50Hz, Relay output SPDT
43	TL41 ON-OFF, supply 85÷250Vac 50Hz, Relay output SPDT
73	ON-OFF TC7.3R local calibration, 24Vdc, 3 relays out for 3 adjustable set-points
99	Special
Housing	
B	IP66 PC polycarbonate loaded
C	IP65 aluminum varnished
D	IP65 double cover PBT
G	IP66 aluminum varnished (necessary for ATEX versions)
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special
Process connection	
02	G1" (G 1 A) / SS316
04	1" NPT / SS316
11	G1"½ (G 1 ½ A) / Carbon-steel
12	G1"½ (G 1 ½ A) / SS316
18	G1"½ (G 1 ½ A) / PVC
19	G1"½ (G 1 ½ A) / PTFE
20	Sanitary DN25 DIN11851, SS304L
21	Sanitary DN40 DIN11851, SS304L
22	Sanitary DN50 DIN11851, SS304L
42	Flange DN40 PN16, Carbon-steel
50	Flange DN40 PN16, SS304
51	Flange DN40 PN16, SS316
52	Flange DN50 PN16 DIN2527 form B (without gasket), SS316
53	Flange DN80 PN16 DIN2527 form B (without gasket), SS316
54	Flange DN100 PN16 DIN2527 form B (without gasket), SS316
60	Flange ANSI RF 2" 150psi, SS316
61	Flange ANSI RF 3" 150psi, SS316
62	Flange ANSI RF 4" 150psi, SS316
71	CLAMP 1" SS316



Capacitive


59

73	CLAMP 1 1/2" SS316
75	CLAMP 2" SS316
99	Special

Electrode type and insulation	
B	Ø2,5mm PVC insulated, counterweight in SS316
C	Ø2,5mm PTFE insulated, counterweight in SS316
L	Ø2,5mm PVC insulated, counterweight in PVC
M	Ø2,5mm PTFE insulated, counterweight in PTFE
Z	Special

L= Electrode length, price each meter	
81	Ø2,5mm PVC insulated
82	Ø2,5mm PTFE insulated
99	Special

L1 = non sensitive part (rod), material and price each 10cm	
A	Standard
C	SS316
Z	Special



Capacitive



CLS9

Rod level switch for plastic tanks

ON/OFF capacitive level control; L = 150mm
Suitable for chemical products, acids and others
Top and lateral side plastic tanks-installation


Version	
A	Without electronic preamplifier
B	Compact
E	Compact, Zone 20/21 ATEX certificated (TL41 insert only); to be used with "G" housing
Z	Special

Electronic preamplifier	
00	None
33	TL31R ON-OFF local sensibility calibration supply 24Vdc, Relay output SPDT
34	TL31R ON-OFF local sensibility calibration supply 24Vac, Relay output SPDT
35	TL31R ON-OFF local sensibility calibration supply 115Vac, Relay output SPDT
36	TL31R ON-OFF local sensibility calibration supply 230Vac, Relay output SPDT
41	TL41 ON-OFF, supply 20÷32Vdc / 24Vac 50Hz, Relay output SPDT
43	TL41 ON-OFF, supply 85÷250Vac 50Hz, Relay output SPDT
99	Special

Housing	
B	PC polycarbonate loaded; IP66
C	Diecast aluminum varnished; IP66
D	Double cover PBT; IP65
G	IP66 aluminum varnished (necessary for ATEX versions)
H	IP66 PC with aluminum adapter, 4 holes flange
Z	Special

Process connection	
05	G1" (G 1 A) PVC
06	G1" (G 1 A) PP
18	G1"½ (G 1 ½ A) / PVC
23	G1"½ (G 1 ½ A) / PP
40	Flange DN40 PN6 PVC (Threaded+welded)
43	DN40 PN6 PP (Threaded+welded)
99	Special

Electrode type and insulation	
B	PVC totally insulated - Ø44mm (G1"½) Ø30mm (G1")
C	PP totally insulated - Ø44mm (G1"½) Ø30mm (G1")
Z	Special





CLN Electrode for well and borehole

Base	
CLN	ON/OFF conductive level control electrode, to be fixed to the connection cable (not included) SS316 coaxial insulating pipe to avoid short circuits with other electrode Electrode material SS316 Ø 6mm



PS33 3 rods electrode

Base	
PS33	Conductive level control G ½" A / PVC process connection IP20 mechanical protection Electrodes SS316, Ø4mm, L=300mm electrodes Working temperature up to 60°C

PS310 3 rods electrode

Base	
PS310	Conductive level control G ½" A / PVC process connection IP20 mechanical protection Electrodes in SS316, Ø4mm, L=1000mm electrodes Working temperature up to 60°C



SL PTFE insulated electrode

Conductive level control; Suitable for boiler and autoclave
G 3/8 A / AISI316 process connection
SS316 Ø6mm electrode
IP00 mechanical protection; Max press.10bar
Working temperature up to 180°C

L= Electrode length	
030	L = 300mm
050	L = 500mm
070	L = 700mm
100	L = 1000mm



SL

**SU**

PTFE insulated electrode

Conductive level control; suitable for boiler and autoclave
 G 3/8" A / AISI316 process connection
 PTFE insulated SS316 Ø6mm electrode
 IP00 mechanical protection; Max press.25bar
 Working temperature up to 180°C

L= Electrode length	
056	L = 56mm
5M thread	
A	None
B	5M thread on top

RL2

PTFE insulated electrode

Base	
RL2	Conductive level control G 3/8" A / SS316 process connection Terminal part in SS316, Ø5mm L=105mm Working temperature up to 50°C



RL2



RL5

RL3

Multi rods electrode

Conductive level control;
 max 5 rods
 Max electrode length: 3m

Housing	
B	PVC black; IP66
Process connection	
18	G 1" ½ A / Black PVC
Electrode n.	
D	n.3; Ø6mm
F	n.5; Ø6mm
Optional (opt.)	
0	None
1	L = 1m Ø6mm rod - unit price
2	L = 2m Ø6mm rod - unit price
3	L = 3m Ø6mm rod - unit price
4	PVC spacer

RL5

Ceramic insulated electrode with fibre glass

Base	
RL5	Conductive level control G ½" A / SS316 process connection Terminal part in SS316, Ø15mm L=65mm Working temperature up to 280°C, max press. 25bar



RL6

Multi rods electrode

Conductive level control; max 5 rods
Max electrode length: 3m

Housing	
B	Polycarbonate loaded; IP66
E	DIN B aluminum painted (n.1 electrode selection available); IP66
G	DIN A aluminum painted; IP66
Z	Special

Process connection	
02	G 1 A / SS316, max 3 rods Ø5mm
04	1" NPT-M / SS316, max 3 rods Ø5mm
05	G 1 A / PVC, max 3 rods Ø5mm
12	G 1 ½ A / SS316, not available for head connection DIN B
18	G 1 ½ A / PVC, not available for head connection DIN B
20	DN25 DIN11851 SS304L (sanitary) 1 rod only "B"
21	DN40 DIN11851 SS304L (sanitary)
22	DN50 DIN11851 SS304L (sanitary)
71	Clamp 1" material SS316
73	Clamp 1 1/2" material SS316, not available for head connection DIN B
75	Clamp 2" material SS316, not available for head connection DIN B
84	G ½ A / SS316, only with head connection DIN B - only one rod
85	1/2" NPT-M / SS316, only with head connection DIN B - only one rod
92	G 3/4 A / SS316, max 1 rod Ø10mm - head connection DIN B
93	3/4" NPT-M / SS316, max 1 rod Ø10mm - head connection DIN B
94	G 3/4 A / PVC, max 2 rods Ø5mm
99	Special

Electrode n.	
B	n.1
C	n.2 Ø5mm only for process fitting cod. 02, 04, 05, 12, 18, 20, 21, 22, 71, 73, 75
D	n.3; Ø5mm only for process fitting cod. 02, 04, 05, 12, 18, 21, 22, 73, 75
E	n.4; Ø5mm only, only for process fitting cod. 12, 18, 21, 22, 71, 73, 75
F	n.5; Ø5mm only, only for process fitting cod. 12, 18, 21, 22, 71, 73, 75
Z	Special

Electrode types and insulation, price per 100mm of each electrode (max 3m)	
36	Ø5mm SS316 rod
37	PVC coated Ø5mm SS316 rod
38	PTFE coated Ø5mm SS316 rod
39	FEP lined Ø5mm SS316 rod
40	Ø10mm SS316 rod, only one electrode per sensor possible
41	PVC coated Ø10mm SS316 rod, only one electrode per sensor possible
44	PTFE coated Ø10mm SS316 rod, only one electrode per sensor possible
99	Special





RL8

Multi ropes electrode

Conductive level control; max. 5 ropes
Max electrodes length 300m

Housing	
B	Polycarbonate loaded; IP66
G	DIN A aluminum painted; IP66
Z	Special
Process connection	
02	G 1 A / SS316
04	1" NPT-M / SS316
05	G 1 A / PVC
12	G 1 ½ A / SS316
18	G 1 ½ A / PVC
19	G 1 ½ A / PTFE
71	Clamp 1" / SS316
73	Clamp 1 1/2" / SS316
75	Camp 2" / SS316
99	Special
Electrode n.	
B	n.1
C	n.2
D	n.3
E	n.4; only for connection cod. 18, 73, 75
H	n.5; only for connection cod. 18, 73, 75
Z	Special
Rope type, price per meter of each electrode	
81	PVC insulated Ø2,5mm SS316
82	PTFE insulated Ø2,5mm SS316
99	Special








RAL04

Unit for level conductive electrodes

Conductive level control up to 4 single setpoint
AC control electrode voltage
N.4 SPDT 3A/250Vac contact (1 for setpoint)
Working temperature -20 + 60°C

Version	
B	DIN rail enclosure IP10
Z	Special
Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz




RAL11

Unit for level conductive electrodes

Min/max conductive level control or pump control
Alternate control voltage to the electrodes
2 relays SPDT contacts 3A/250Vac - Adj.sensibility
Undecal plug-in male-socket; IP40 frontal
Working temperature -20 +50°C

Version	
A	Standard
B	IP66
Z	Special
Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz
Accessories	
A	None
B	Undecal socket + fixing spring
Z	Special



Conductive



RAL12

Unit for level conductive electrodes

Min/max conductive level control; adj.sensibility
 Alternate control voltage to the electrodes
 Control of the electrodes electrical connection "security relay"
 N1 level control relay; SPDT contacts 3A/250Vac
 N1 safety relay; SPDT contacts 3A/250Vac
 Undecal plug-in male-socket; IP40 frontal
 Working temperature -20 +50°C

Version	
A	Standard
B	IP66
Z	Special

Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz

Accessories	
A	None
B	Undecal socket + fixing spring
Z	Special

RAL13


Unit for level conductive electrodes

Min/max conductive level control or pump control
 Alternate control voltage to the electrodes
 2 relays SPDT contacts 3A/250Vac
 Adj. sensibility and delay time
 Undecal plug-in male-socket; IP40 frontal
 Working temperature -20 +50°C

Version	
A	Standard
B	IP66
Z	Special

Power supply	
0	24Vac 50÷60Hz
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz
4	24Vdc

Accessories	
A	None
B	Undecal socket + fixing spring
Z	Special





RSL200



Diapason level switch for granulates and powders

Process connection, G 1 1/2" A/ SS316
 Product temperature range from -20 to 140°C
 IP66 mechanical protection
 Insertion length 202mm (fork 155mm)
 Power supply: 20÷36Vdc / 20÷255Vac 50Hz
 0,8W or 15VA max power consumption
 Relay output rating 250Vac, 2A

Version	
A	Compact
B	Rigid extension, price each 100mm (min. length 200mm - max. 3000mm)
C	Rope extension, price each meter (min. length 1m - max. 30m)
E	Compact + transparent cap
Z	Special

Certification	
0	None - with IP66 PC (loaded-polycarbonate)
1	22 Zone - with IP66 PC (loaded-polycarbonate)
2	Atex II 1/2D Ex tD A20/21 IP66 T 150 (zone 20/21) - with aluminum housing

Output	
A	N. 1 SPDT relay






RSL201

Vibrating rod level switch for granulates and powders

Process connection: G 1½" A / SS316
 Product temperature range: -20 ÷ +140°C
 IP66 mechanical protection
 Rod length: 160mm
 Power supply: 20÷36Vdc / 20÷255Vac 50Hz
 0,8 or 15VA max power consumption
 Relay output rating 250Vac, 2A

Version	
A	Compact
C	Rope extension, price each meter (min. length 1m - max 30m)
E	Compact + transparent cap
Z	Special
Certification	
0	None - with IP66 PC (loaded-polycarbonate)
1	22 Zone - with IP66 PC (loaded-polycarbonate)
2	Atex II 1/2D Ex tD A20/21 IP66 T 150 (zone 20/21) - with aluminum housing
Output	
A	N. 1 SPDT relay



Accessories and spare parts

69

CRA

Capacitive, conductive and radar system accessories



Optional (opt.)	
010D029A	RS485 communication software for TC22/30
306A007A	Coaxial cable with double shield with cable butting; L=1,5m; 200°C
306A008A	Coaxial cable with double shield with cable butting; L=2m; 200°C
306A010A	Double shield coax. cable butting
306A011A	RG62 coax. cable butting
395A002D	Keyboard/display programming module VL601 for radar and ultrasonic
400A001C	SS316 L=1m rod extension
400A002C	6mm carbon-steel rope extension with threaded connection and counter-weight - L=3m
400A080C	SS316 rod L = 1m Ø6mm for RL3
400A081C	SS316 rod L = 2m Ø6mm for RL3
400A082C	SS316 rod L = 3m Ø6mm for RL3
400B001C	StainlessSteelwith brass ring welded, holes top/botton L=1000mm
410A001B	Interconnection printed-board for remote version (CLT,CLS and conductive)
525A001F	Coax. cable for separate version TC serie (price per meter)
525A001H	Coax. cable with double shield (max 3m); price per meter
525A003E	Coax. cable with double shield (max 3m); max. temp. 120°C; price per meter
585B005P	PTFE spreader for rods
585B005R	PVC spreader for rods
585B007R	PVC spacer for RL3
618A001A	Wing-nut for CLAMP 1" or 1 1/2" in SS304
618A002A	Wing-nut for CLAMP 2" in SS304
640C001A	Gasket Viton / PTFE for CLAMP 1 1/2"
640C002A	Gasket Viton / PTFE for CLAMP 2"
822A001C	Sensitized for Ø15mm SS316 Electrode
845A007A	Plug for CLAMP 1 1/2" in SS304
845A007C	Plug for CLAMP 1 1/2" in SS316
845A008C	Plug for CLAMP 2" in SS316
850A002B	Customer code identification label 18 characters SS316
886A001A	Fixing pipe for CLAMP 1" or 1 1/2" in SS304
886A001C	Fixing pipe for CLAMP 1 1/2" in SS316
886A002A	Fixing pipe for CLAMP 2" in SS304
886A002C	Fixing pipe for CLAMP 2" in SS316
902B008A	Calibration certificate with 5% water in biodegradable oil (PANOLIN)
902C008A	Calibration certificate with 5% water in mineral oil

Accessories and spare parts

CRSP

Radar, capacitive, conductive and vibration spare parts

Spare parts	
400A002B	TC20, 4÷20mA, "C", Calibration with dip-switches, 24Vdc; Out 4÷20mA, to be connect to CA101 unit
400A022B	TL31R ON-OFF Local sensibility calibration supply 24 Vdc, Relay output SPDT
400A023B	TL31R ON-OFF Local sensibility calibration supply 24 Vac, Relay output SPDT
400A024B	TL31R ON-OFF Local sensibility calibration supply 115 Vac, Relay output SPDT
400A025B	TL31R ON-OFF Local sensibility calibration supply 230 Vac, Relay output SPDT
400A026B	TC7.3R local calibration, 24Vdc, 3 relays out for 3 adjustable set-points
400A050B	TC21, 4÷20mA, Calibration with dip-switches and trim, 24Vdc, "C"
400A054B	TC30, 4÷20mA, 2 push-buttons calibration, 2 wires, 24Vdc EExia II
400A055B	TC30, 4÷20mA, 2 push-buttons calibration, 2 wires, 24Vdc
400A060B	TL41, 2 push-buttons sensibility calibration, 85÷250Vac 50Hz, relay output SPDT
400A061B	LV1 preamplifier insert for vibration probe, relay output
400A072B	TC22, 4÷20mA, Lowcost micro-p based, 2 push buttons for calibration, 24Vdc.
400A073B	TC23, 4÷20mA, Lowcost micro-p based, 2 push buttons for calibration, 24Vac.
400A074B	TC24, 4÷20mA, Lowcost micro-p based, 2 push buttons for calibration, 115Vac.
400A075B	TC25, 4÷20mA, Lowcost micro-p based, 2 push buttons for calibration, 230Vac.
400A076B	TC26, 4÷20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 24Vdc
400A077B	TC27, 4÷20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 24Vac
400A078B	TC28, 4÷20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 115Vac
400A079B	TC29, 4÷20mA, 2 push-buttons calibration, 1relay, RS485 for SMART calibration, 230Vac
400B061B	LV1 preamplifier insert for vibration probe, static output
400C060B	TL41, 2 push-buttons sensibility calibration, 20÷30Vdc/24Vac 50Hz, relay output SPDT
410A001B	Interconnection printed-board for remote version (CLT,CLS and conductive)
452A001A	Ø4mm SS316 rope, with counterweight and process connection eur 110,00 + rope price/mt
452A002A	Ø6mm SS316 rope, with counterweight and process connection eur 130,00 + rope price/mt
490A001C	PC polycarbonate loaded head connection
490A002C	Diecast aluminum varnished head connection
490A004C	DIN A aluminum head connection
490A005C	DIN B aluminum head connection
490A007C	DIN B PA (poliammide) head connection
490A020C	PBT complete head connection
490B020C	Separate head connection for pin insert connection (TL31, TC73R)
490C020C	Separate head connection for bajonet insert connection (TC22÷30)
490C030C	RSL200 compact version mechanic without preamplifier insert
490S024C	TC/TL41 aluminum adapter without flange
490S025C	PC polycarbonate head (mod H) + aluminum adapter with 4 holes square flange
545A007N	CE11 plastic enclosure
546A070N	Transparent cap for PC housing "F"
546B001N	PC (loaded-polycarbonate) head connection transparent cap
546B003N	PBT loaded head connection transparent cap
715A013A	IP66 gland PG13,5 for 8-13mm cable
810A011F	Bajonet bolt
830A001X	UNDECAL plug
899F001A	UNDECAL socket + fixing spring




Open channel

71

FLOWMETER Ultrasonic open channel flow control unit

Compact - Suitable for upstream installation in weir and Venturi (standard and non-standard)
 4÷20mA output with instantaneous flow transmission
 Relay nr. 1 for impulses/volume transmission
 Relay nr. 2 for threshold alarm or diagnostic
 MODBUS RTU output
 Temperature range : -30° ÷ +70°C (80° non continuous)



Version	
0	4-wire, MODBUS, range 5m
9	Special
Housing / Sensor materials	
F	PC with transparent cap, IP67 / PP
U	Aluminum with transparent cap, IP67 / PP
Z	Special
Power supply	
4	24Vdc (20÷30Vdc)
5	12Vdc (max 20Vdc)
9	Special
Optional (opt.)	
A	None
C	DN80 PN6 UNI 6091-71/PP flange
D	VL601 keyboard/display programming module
H	2" BSP/PP fixing bolt
S	MODBUS RTU communication software (010F119A)
Z	Special




F Housing cod.



U Housing cod.



MUDBUS
S/W PC



Open channel



OC1000

Control unit for open channels flow measurement

Measurement ranges: Flow 0 ÷ 9999 mc/h

Level 0.3 ÷ 5mt - Resolution: ± 0.01 mt - Accuracy: $\pm 0.2\%$ F.S.


Temperature -25 ÷ +75°C - Resolution: 1°C - Accuracy: 1% F.S.

Selectable engineering flow rate units: Flow (mc/h), Level (mt, cm, mm), Temperature (°C)

Direct mathematical computation for rectangular weirs, Cipolletti, Thompson,



Venturi flumes, Parshall, Leopold Lagco.

Version	
A	IP65 for field mounting
Relay	
5	5 relays SPDT
Power supply	
5	90 ÷ 260 Vac
Output	
C	Nr. 2 analogic outputs
Field Bus	
1	RS485 MODBUS



**FLOW MEASUREMENT
WITH VENTURI CHANNEL**

ULTRASONIC AND PIEZOMETER LEVEL MEASUREMENT





Open channel

73

BS150**Pre-fabricated Venturi flumes**

$Q_{min}=1\text{m}^3/\text{h} - 0,28\text{l}/\text{sec}$; $Q_{max}=50\text{m}^3/\text{h} - 13,8\text{l}/\text{s}$
Length 0,480m; width 0,15m; high 0,27m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
Z	Special

BS200**Pre-fabricated Venturi flumes**

$Q_{min}=2\text{m}^3/\text{h} - 0,55\text{l}/\text{sec}$; $Q_{max}=55\text{m}^3/\text{h} - 15,27\text{l}/\text{s}$
Length 0,639m; width 0,2m; high 0,24m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
Z	Special

BS300**Pre-fabricated Venturi flumes**

$Q_{min}=3\text{m}^3/\text{h} - 0,83\text{l}/\text{sec}$; $Q_{max}=150\text{m}^3/\text{h} - 41,6\text{l}/\text{s}$
Length 0,958m; width 0,3m; high 0,36m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
I	650D012A, wooden crate
Z	Special

BS400**Pre-fabricated Venturi flumes**

$Q_{min}=10\text{m}^3/\text{h} - 2,7\text{l}/\text{sec}$; $Q_{max}=310\text{m}^3/\text{h} - 86,1\text{l}/\text{s}$
Length 1,278m; width 0,4m; high 0,48m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
I	650D012A, wooden crate
Z	Special

Open channel



BS500

Pre-fabricated Venturi flumes

$Q_{min}=20\text{m}^3/\text{h}$ - 5,5l/sec; $Q_{max}=500\text{m}^3/\text{h}$ - 138,8l/s
Length 1,598m; width 0,5m; high 0,60m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
I	650D012A, wood case
Z	Special

BS600

Pre-fabricated Venturi flumes

$Q_{min}=25\text{m}^3/\text{h}$ - 7,15l/sec; $Q_{max}=850\text{m}^3/\text{h}$ - 236l/s
Length 1,5m; width 0,6m; high 0,72m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
I	650D012A, wooden crate
Z	Special

BS800

Pre-fabricated Venturi flumes

$Q_{min}=50\text{m}^3/\text{h}$ - 13,9l/sec; $Q_{max}=1400\text{m}^3/\text{h}$ - 389l/s
Length 2m; width 0,8m; high 0,90m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
I	650D012A, wooden crate
Z	Special

BS1000

Pre-fabricated Venturi flumes

$Q_{min}=60\text{m}^3/\text{h}$ - 16,6l/sec; $Q_{max}=2250\text{m}^3/\text{h}$ - 625l/s
Length 2,5m; width 1m; high 1m

Construction materials	
P	PP Polypropilen
Z	Special
Accessories	
A	None
I	650D012A, wooden crate
Z	Special



Open channel

75




Fig. 1







Fig. 2



Venturi flumes overall and installation dimensions

L1 is the extension joint flume dimension only for BS600+1000 models (see fig1 for BS150+500 and fig.2 for BS600+1000)

Dim. Model	L	L1	H	E	b0	b1	X	Y	S
BS150	479		270	5	150	60	483	280	7
BS200	639		240	5	200	80	645	250	7
BS300	958		360	6	300	120	968	370	8
BS400	1277		480	8	400	160	1281	490	10
BS500	1597		600	8	500	200	1617	610	10
BS600	1500	416	720	10	600	240	1520	740	14
BS800	2000	555	900	10	800	320	2030	920	14
BS1000	2500	694	1000	15	1000	400	2550	1020	19

Open channel


**PB**

Pre-fabricated Palmer-Bowlus flumes

Insertion installation in already in place pipes

Linking with FLOWMETER ultrasonic flow transmitter or SWING unit

DN pipe (mm)	
150	DN150 ÷ DN200 (6" ÷ 8")
Construction materials	
A	Fiberglass
Z	Special
Accessories	
0	None
9	Special

**CAL**

Non standard weirs and flume, flow calculation

Base	
CAL	Calculation sheet with table and graphic



Electromagnetic

77

RPmag62

Electromagnetic Flowmeter

For conductive fluids even with a content of suspended matters

Medium ambient temperature range: -20° ÷ 70°C

Housing protection degree for electronic: IP67

Version	
F	Remote - 5m standard cable length (over 5m euro 13,00 each additional meter)
Y	Compact
DN flange / Max. pressure / Lining	
001013	DN10 / 4,0MPa / FEP (-40° ÷ +150°C); range 0,14 ÷ 2,9m3/h; UNI 1092-1 standard
001513	DN15 / 4,0MPa / PTFE (-40° ÷ +150°C); range 0,3 ÷ 6m3/h; UNI 1092-1 standard
002513	DN25 / 4,0MPa / PTFE (-40° ÷ +150°C); range 0,6 ÷ 11m3/h; UNI 1092-1 standard
003213	DN32 / 4,0MPa / PTFE (-40° ÷ +150°C); range 1 ÷ 25m3/h; UNI 1092-1 standard
004013	DN40 / 4,0MPa / PTFE (-40° ÷ +150°C); range 1,8 ÷ 36m3/h; UNI 1092-1 standard
005011	DN50 / 4,0MPa / rubber (-10° ÷ +80°C); range 3 ÷ 60m3/h; UNI 1092-1 standard
005013	DN50 / 4,0MPa / PTFE (-40° ÷ +150°C); range 3 ÷ 60m3/h; UNI 1092-1 standard
006511	DN65 / 4,0MPa / rubber (-10° ÷ +80°C); range 5,8 ÷ 126m3/h; UNI 1092-1 standard
006513	DN65 / 4,0MPa / PTFE (-40° ÷ +150°C); range 5,8 ÷ 126m3/h; UNI 1092-1 standard
008011	DN80 / 4,0MPa / rubber (-10° ÷ +80°C); range 8,9 ÷ 180m3/h; UNI 1092-1 standard
008013	DN80 / 4,0MPa / PTFE (-40° ÷ +150°C); range 8,9 ÷ 180m3/h; UNI 1092-1 standard
010011	DN100 / 4,0MPa / rubber (-10° ÷ +80°C); range 11 ÷ 250m3/h; UNI 1092-1 standard
010013	DN100 / 4,0MPa / PTFE (-40° ÷ +150°C); range 11 ÷ 250m3/h; UNI 1092-1 standard
010041	DN100 / 1,6MPa / Rubber (-10° ÷ +80°C); range 11 ÷ 250m3/h; UNI 1092-1 standard
010043	DN100 / 1,6MPa / PTFE (-40° ÷ +150°C); range 11 ÷ 250m3/h; UNI 1092-1 standard
012511	DN125 / 4,0MPa / rubber (-10° ÷ +80°C); range 20 ÷ 400m3/h; UNI 1092-1 standard
012513	DN125 / 4,0MPa / PTFE (-40° ÷ +150°C); range 20 ÷ 400m3/h; UNI 1092-1 standard
012541	DN125 / 1,6MPa / Rubber (-10° ÷ +80°C); range 20 ÷ 400m3/h; UNI 1092-1 standard
012543	DN125 / 1,6MPa / PTFE (-40° ÷ +150°C); range 20 ÷ 400m3/h; UNI 1092-1 standard
015011	DN150 / 4,0MPa / rubber (-10° ÷ +80°C); range 30 ÷ 600m3/h; UNI 1092-1 standard
015013	DN150 / 4,0MPa / PTFE (-40° ÷ +150°C); range 30 ÷ 600m3/h; UNI 1092-1 standard
015041	DN150 / 1,6MPa / Rubber (-10° ÷ +80°C); range 30 ÷ 600m3/h; UNI 1092-1 standard
015043	DN150 / 1,6MPa / PTFE (-40° ÷ +150°C); range 30 ÷ 600m3/h; UNI 1092-1 standard
020021	DN200 / 1,0MPa / rubber (-10° ÷ +80°C); range 50 ÷ 1000m3/h; UNI 1092-1 standard
020023	DN200 / 1,0MPa / PTFE (-40° ÷ +150°C); range 50 ÷ 1000m3/h; UNI 1092-1 standard
020041	DN200 / 1,6MPa / rubber (-10° ÷ +80°C); range 50 ÷ 1000m3/h; UNI 1092-1 standard
020043	DN200 / 1,6MPa / PTFE (-40° ÷ +150°C); range 50 ÷ 1000m3/h; UNI 1092-1 standard
025021	DN250 / 1,0MPa / rubber (-10° ÷ +80°C); range 85 ÷ 1800m3/h; UNI 1092-1 standard
025023	DN250 / 1,0MPa / PTFE (-40° ÷ +150°C); range 85 ÷ 1800m3/h; UNI 1092-1 standard
025041	DN250 / 1,6MPa / rubber (-10° ÷ +80°C); range 85 ÷ 1800m3/h; UNI 1092-1 standard
025043	DN250 / 1,6MPa / PTFE (-40° ÷ +150°C); range 85 ÷ 1800m3/h; UNI 1092-1 standard
030021	DN300 / 1,0MPa / rubber (-10° ÷ +80°C); range 110 ÷ 2500m3/h; UNI 1092-1 standard
030023	DN300 / 1,0MPa / PTFE (-40° ÷ +150°C); range 110 ÷ 2500m3/h; UNI 1092-1 standard
030041	DN300 / 1,6MPa / rubber (-10° ÷ +80°C); range 110 ÷ 2500m3/h; UNI 1092-1 standard
030043	DN300 / 1,6MPa / PTFE (-40° ÷ +150°C); range 110 ÷ 2500m3/h; UNI 1092-1 standard
035021	DN350 / 1,0MPa / rubber (-10° ÷ +80°C); range 180 ÷ 3200m3/h; UNI 1092-1 standard
035023	DN350 / 1,0MPa / PTFE (-40° ÷ +150°C); range 180 ÷ 3200m3/h; UNI 1092-1 standard
035041	DN350 / 1,6MPa / rubber (-10° ÷ +80°C); range 180 ÷ 3200m3/h; UNI 1092-1 standard
035043	DN350 / 1,6MPa / PTFE (-40° ÷ +150°C); range 180 ÷ 3200m3/h; UNI 1092-1 standard
040021	DN400 / 1,0MPa / rubber (-10° ÷ +80°C); range 220 ÷ 4500m3/h; UNI 1092-1 standard
040023	DN400 / 1,0MPa / PTFE (-40° ÷ +150°C); range 220 ÷ 4500m3/h; UNI 1092-1 standard
040041	DN400 / 1,6MPa / rubber (-10° ÷ +80°C); range 220 ÷ 4500m3/h; UNI 1092-1 standard
040043	DN400 / 1,6MPa / PTFE (-40° ÷ +150°C); range 220 ÷ 4500m3/h; UNI 1092-1 standard
045021	DN450 / 1,0MPa / rubber (-10° ÷ +80°C); range 270 ÷ 6000m3/h; UNI 1092-1 standard
045023	DN450 / 1,0MPa / PTFE (-40° ÷ +150°C); range 270 ÷ 6000m3/h; UNI 1092-1 standard
045041	DN450 / 1,6MPa / rubber (-10° ÷ +80°C); range 270 ÷ 6000m3/h; UNI 1092-1 standard
045043	DN450 / 1,6MPa / PTFE (-40° ÷ +150°C); range 270 ÷ 6000m3/h; UNI 1092-1 standard

Electromagnetic



050021	DN500 / 1,0MPa / rubber (-10° ÷ +80°C); range 320 ÷ 6500m³/h; UNI 1092-1 standard
050023	DN500 / 1,0MPa / PTFE (-40° ÷ +150°C); range 320 ÷ 6500m³/h; UNI 1092-1 standard
060021	DN600 / 1,0MPa / rubber (-10° ÷ +80°C); range 490 ÷ 9500m³/h; UNI 1092-1 standard
060023	DN600 / 1,0MPa / PTFE (-40° ÷ +150°C); range 490 ÷ 9500m³/h; UNI 1092-1 standard
070021	DN700 / 1,0MPa / rubber (-10° ÷ +80°C); range 680 ÷ 12600m³/h; UNI 1092-1 standard
070023	DN700 / 1,0MPa / PTFE (-40° ÷ +150°C); range 680 ÷ 12600m³/h; UNI 1092-1 standard
080021	DN800 / 1,0MPa / rubber (-10° ÷ +80°C); range 900 ÷ 17600m³/h; UNI 1092-1 standard
080023	DN800 / 1,0MPa / PTFE (-40° ÷ +150°C); range 900 ÷ 17600m³/h; UNI 1092-1 standard
090021	DN900 / 1,0MPa / rubber (-10° ÷ +80°C); range 1200 ÷ 25200m³/h; UNI 1092-1 standard
090023	DN900 / 1,0MPa / PTFE (-40° ÷ +150°C); range 1200 ÷ 25200m³/h; UNI 1092-1 standard
100021	DN1000 / 1,0MPa / rubber (-10° ÷ +80°C); range 1450 ÷ 27000m³/h; UNI 2223 standard
100023	DN1000 / 1,0MPa / PTFE (-40° ÷ +150°C); range 1450 ÷ 27000m³/h; UNI 1092-1 standard
120031	DN1200 / 0,6MPa / rubber (-10° ÷ +80°C); range 2000 ÷ 40000m³/h; UNI 1092-1 standard
140031	DN1400 / 0,6MPa / rubber (-10° ÷ +80°C); range 2900 ÷ 51000m³/h; UNI 1092-1 standard
160031	DN1600 / 0,6MPa / rubber (-10° ÷ +80°C); range 3800 ÷ 70000m³/h; UNI 1092-1 standard
999999	Special / Special / Special

Electrodes material

1	316SST stainless steel
2	Hastelloy B
3	Hastelloy C
4	Titanium
5	Tantalum

Power supply

1	85÷265Vac 50÷60Hz
2	24Vdc
3	24Vac
9	Special

Accessories

0	None
1	321SS or Hastelloy C grounding rings for plastic pipe installation (price on request)
2	Protective rings (price on request)
3	3 electrodes (from DN50 to DN300 for PTFE - fm DN100 on for rubber) - price on request
8	Standard ANSI flanges (price on request);no surcharge up to 6" (DN150)

Output

1	Standard (4÷20mA) + pulse output
2	4÷20Ma + pulse + RS485
3	4÷20mA + pulse + HART
4	4÷20Ma + pulse + PROFIBUS
5	4÷20Ma + pulse + MODBUS RTU

Pipe protection degree



1	IP67
2	IP68 (for remote version only)





Electromagnetic

79



Electromagnetic



Smag62

Electromagnetic Flowmeter

With sensor body in SS304
For conductive fluids even with a content of suspended matters.
For chemical/pharmaceutical and food applications

Version	
F	Remote - 5m standard cable length (over 5m euro 12,50 each additional meter)
Y	Compact
DN flange / Max. pressure / Lining	
0010E2	DN10 / 1.6MPa / PFA
0010E3	DN10 / 1.6MPa / PTFE
0015E2	DN15 / 1.6MPa / PFA
0015E3	DN15 / 1.6MPa / PTFE
0020E2	DN20 / 1.6MPa / PFA
0020E3	DN20 / 1.6MPa / PTFE
0025E2	DN25 / 1.6MPa / PFA
0025E3	DN25 / 1.6MPa / PTFE
0032E2	DN32 / 1.6MPa / PFA
0032E3	DN32 / 1.6MPa / PTFE
0040E2	DN40 / 1.6MPa / PFA
0040E3	DN40 / 1.6MPa / PTFE
0050E2	DN50 / 1.6MPa / PFA
0050E3	DN50 / 1.6MPa / PTFE
0065E2	DN65 / 1.6MPa / PFA
0065E3	DN65 / 1.6MPa / PTFE
0080E2	DN80 / 1.6MPa / PFA
0080E3	DN80 / 1.6MPa / PTFE
0100E2	DN100 / 1.6MPa / PFA
0100E3	DN100 / 1.6MPa / PTFE
0125E2	DN125 / 1.6MPa / PFA
0125E3	DN125 / 1.6MPa / PTFE
0150E2	DN150 / 1.6MPa / PFA
0150E3	DN150 / 1.6MPa / PTFE
Process connection	
D	DIN 11851 flange
E	DIN SS304 CLAMP flange ISO2852
Electrodes material	
1	316SST stainless steel
3	Hastelloy C
4	Titanium
5	Tantalum
9	Special
Power supply	
A	85÷265Vac 50÷60Hz
Z	Special
Accessories	
0	None
Output	
A	Standard (4÷20mA) + pulse output



Electromagnetic

81

Pipe protection degree	
1	IP67
2	IP68 (only for remote version)
Fluid temperature	
A	$\leq 120^{\circ}\text{C}$ (only for remote version)
B	$\leq 150^{\circ}\text{C}$ (only for remote version - prices on request)
C	Standard ($-20 \div +60^{\circ}\text{C}$)



Electromagnetic



Pmag

Electromagnetic flowmeter

For conductive fluids even with a content of suspended matters
Medium ambient temperature range: -20° ÷ 75°C
Housing protection degree for electronic: IP67

Version	
F	Remote - standard cable length 5m (over 5m eur 7,00 each additional meter)
Y	Compact
DN flange / Max. pressure / Lining	
0010B2	DN10 / 4.0MPa / PTFE
0010E2	DN10 / 1.6MPa / PTFE
0015B2	DN15 / 4.0MPa / PTFE
0015E2	DN15 / 1.6MPa / PTFE
0020B2	DN20 / 4.0MPa / PTFE
0020E2	DN20 / 1.6MPa / PTFE
0025B2	DN25 / 4.0MPa / PTFE
0025E2	DN25 / 1.6MPa / PTFE
0032B2	DN32 / 4.0MPa / PTFE
0032E2	DN32 / 1.6MPa / PTFE
0040B1	DN40 / 4.0MPa / Rubber
0040E1	DN40 / 1.6MPa / Rubber
0050B1	DN50 / 4.0MPa / Rubber
0050E1	DN50 / 1.6MPa / Rubber
0065B1	DN65 / 4.0MPa / Rubber
0065E1	DN65 / 1.6MPa / Rubber
0080B1	DN80 / 4.0MPa / Rubber
0080E1	DN80 / 1.6MPa / Rubber
0100B1	DN100 / 4.0MPa / Rubber
0100E1	DN100 / 1.6MPa / Rubber
0125B1	DN125 / 4.0MPa / Rubber
0125E1	DN125 / 1.6MPa / Rubber
0150B1	DN150 / 4.0MPa / Rubber
0150E1	DN150 / 1.6MPa / Rubber
0200C1	DN200 / 1.0MPa / Rubber
0200E1	DN200 / 1.6MPa / Rubber
0250C1	DN250 / 1.0MPa / Rubber
0250E1	DN250 / 1.6MPa / Rubber
0300C1	DN300 / 1.0MPa / Rubber
0300E1	DN300 / 1.6MPa / Rubber
0350C1	DN350 / 1.0MPa / Rubber
0350E1	DN350 / 1.6MPa / Rubber
0400C1	DN400 / 1.0MPa / Rubber
0400E1	DN400 / 1.6MPa / Rubber
0450C1	DN450 / 1.0MPa / Rubber
0450E1	DN450 / 1.6MPa / Rubber
0500C1	DN500 / 1.0MPa / Rubber
0500E1	DN500 / 1.6MPa / Rubber
0600C1	DN600 / 1.0MPa / Rubber
0700C1	DN700 / 1.0MPa / Rubber
0800C1	DN800 / 1.0MPa / Rubber
0900C1	DN900 / 1.0MPa / Rubber
1000C1	DN1000 / 1.0MPa / Rubber



Electromagnetic

83

Process connection	
B	DIN (UNI 1092-1) flange
D	ANSI flange (price on request)
Z	Special
Electrodes material	
1	316SST Stainless steel
3	Hastelloy C
Power supply	
A	85÷265Vac
B	24Vdc
Z	Special
Accessories	
0	None
Output	
A	4÷20mA + pulse output
C	4÷20mA + pulse output + HART
E	4÷20mA + pulse + MODBUS RTU
Pipe protection degree	
1	IP67
2	IP68





MSP

Electromagnetic system spare parts

Spare parts	
PMAG62S*****A*A*	Pmag complete converter remote version, 230Vac, 4÷20mA, IP67
RPMAG62S*****1*1	RPmag62 complete converter remote version, 230Vac, 4÷20mA, IP67
RPMAG62S-396A001A	RPmag62 main board
RPMAG62S-396A001D	RPmag62 HART communication board
RPMAG62S-396A001J	RPmag62 power board 24Vac
RPMAG62S-396A001L	Rpmag62 power supply filter module 230V
RPMAG62S-396A002D	RPmag62 RS485 communication board
RPMAG62S-396A002J	RPmag62 power board 24Vdc
RPMAG62S-396A002L	Rpmag62 power supply filter module 24Vdc/24Vac
RPMAG62S-396A003D	RPmag62 PROFIBUS communication board
RPMAG62S-396A003J	RPmag62 power board 230V
RPMAG62S-396A004D	RPmag62 MODBUS communication board
RPMAG62S-496A002B	RPmag62 display
RPMAG62S-525B004A	RPmag62 3 x 1,5mm shielded cable for electrodes, price each meter
RPMAG62S-525B005A	RPmag62 2 x 1,5mm shielded cable for magnetic inductance, price each meter
RPMAG62S-546A001J	RPmag62 blind cover (Ø128mm)
RPMAG62S-546A004J	RPmag62 cover with glass (for display unit version)
SMAG62*****A*A**	SPmag62 complete converter remote version, 230Vac, 4÷20mA, IP67



MA

Electromagnetic system accessories

Optional (opt.)	
RPMAG62S-502A001V	DN15 321SS grounding ring
RPMAG62S-502A002V	DN25 321SS grounding ring
RPMAG62S-502A003V	DN32 321SS grounding ring
RPMAG62S-502A004V	DN40 321SS grounding ring
RPMAG62S-502A005V	DN50 321SS grounding ring
RPMAG62S-502A006V	DN65 321SS grounding ring
RPMAG62S-502A007V	DN80 321SS grounding ring
RPMAG62S-502A009V	DN100 321SS grounding ring
RPMAG62S-502A010V	DN125 321SS grounding ring
RPMAG62S-502A013V	DN150 321SS grounding ring
RPMAG62S-502A014V	DN200 321SS grounding ring
RPMAG62S-502A017V	DN250 321SS grounding ring
RPMAG62S-502A019V	DN300 321SS grounding ring
RPMAG62S-502A020V	DN350 321SS grounding ring
RPMAG62S-502A023V	DN400 321SS grounding ring
RPMAG62S-502A025V	DN450 321SS grounding ring
RPMAG62S-502A026V	DN500 321SS grounding ring
RPMAG62S-502A027V	DN600 321SS grounding ring
RPMAG62S-502A028V	DN700 321SS grounding ring
RPMAG62S-502A029V	DN800 321SS grounding ring
RPMAG62S-502A030V	DN900 321SS grounding ring
RPMAG62S-502A031V	DN1000 321SS grounding ring
RPMAG62S-502A032V	DN1200 321SS grounding ring
RPMAG62S-502A033V	DN1400 321SS grounding ring
RPMAG62S-502A034V	DN1600 321SS grounding ring
RPMAG62S-621A001A	BXF01: Rpmag62 flow simulator, usable with TA-1 Testing Adaptor (855B005A)
RPMAG62S-693A002A	HM-1: HART modem for Rpmag62
RPMAG62S-732A001A	HT-2000: Field Hand Held Communication (HART communicator)
RPMAG62S-855B005A	TA-1: Rpmag62 testing adaptor, usable with BXF01 Rpmag62 flow simulator (621A001A)
RPMAG62S-909B001A	3 points calibration certificate
RPMAG62S-909B002A	5 points calibration certificate

Transit time



SGM-100F Wall mounting transit time ultrasonic flow meter

With clamp-on or insertion transducers.

Speed range: max $\pm 32\text{m/s}$ - Simultaneous display of flowrate and cumulative volume data

Output: 4÷20mA + frequency + 2 relays

Accuracy not better $\pm 1\%$

Transducers connection cable 5 mt

Protection degree: transmitter IP65 - transducers IP68


Supplied with fixing belts for transducers installation

Version	
W	Wall mounting
Z	Special
Power supply	
A	230Vac
D	24Vdc
Z	Special
Transducers	
A0	None
S1	Clamp-on type for pipes DN 15÷100 - 0÷70°C (additional cable eur 8,00 each mt)
SH	Clamp-on type for pipes DN 15÷100 - for high temperature 0÷160°C (additional cable eur 8,00 each mt)
M1	Clamp-on type for pipes DN 50÷700 - 0÷70°C (additional cable eur 8,00 each mt)
MH	Clamp-on type for pipes DN 50÷700 - for high temperature 0÷160°C (additional cable eur 8,00 each mt)
L1	Clamp-on type for pipes DN300÷4000 - 0÷70°C (additional cable eur 8,00 each mt)
I1	Insertion type for steel pipes - 0÷150°C (additional cable eur 8,00 each mt)
I2	Insertion type for cement pipes - 0÷150°C (additional cable eur 8,00 each mt)
Z9	Special
Additional output	
2	RS232
4	RS485
N	None
Z	Special
Optional (opt.)	
A	None
B	RS458 communication software (010D109A)
C	Fixing chain for transducers (5mt) + nr. 2 tie rods
Z	Special



Transit time

87



Transit time



SGM-100H

Portable transit time ultrasonic flow meter

With clamp-on transducers. Data logger built-in up to 2000 reading
Flow measurement for pipes from DN15 to DN4000
Speed range: max $\pm 32\text{m/s}$ - Simultaneous display of flowrate and cumulative volume data
Accuracy not better $\pm 1\%$
Ambient temperature: $-10^{\circ} \div 50^{\circ}\text{C}$ - Humidity $<85\%$ (RH)
Transducers temperature range: $0^{\circ} \div 70^{\circ}\text{C}$ or $0 \div 160^{\circ}\text{C}$ for high temperature
Battery life : 10 hours
Transducers connection cables: 5 mt

Transducers	
S1-	Couple of transducers for pipes from DN15 to DN100 (additional cable eur 8,00 each mt)
M1-	Couple of transducers for pipes from DN50 to DN700 (additional cable eur 8,00 each mt)
L1-	Couple of transducers for pipes from DN300 to DN4000 (additional cable eur 8,00 each mt)
S1F	Couple of transducers on metric frame for pipes from DN15 to DN100 (additional cable eur 8,00 each mt)
M1F	Couple of transducers on metric frame for pipes from DN50 to DN700 (additional cable eur 8,00 each mt)
S1H	Couple of high temperature transducers ($0 \div 150^{\circ}\text{C}$) for pipes from DN15 to DN100 (additional cable eur 8,00 each mt)
M1H	Couple of high temperature transducers ($0 \div 150^{\circ}\text{C}$) for pipes from DN50 to DN700 (additional cable eur 8,00 each mt)
Optional (opt.)	
A	None
B	RS232 communication software (010H108A)
C	Fixing chain for transducers (5mt) + tie rods
D	Grease titanium, high temperature





Transit time

89

SGM-100T Ultrasonic thickness meter

Base	
SGM-100T	<p>Measuring range: 1,2÷225mm, 0,05-9"</p> <p>Materials measured: any hard materials, including steel, cast iron, aluminum, red copper, PVC and other materials</p> <p>Lower limit steel pipes: Ø15x2.0mm, Ø20x3.0mm determined by the transducer</p> <p>Resolution: 0.1mm</p> <p>Accuracy: $\pm(0.5\%n+0.1)$</p> <p>RS232C interface: with RS232C</p> <p>Power supply: 4x1.5V AAA (UM-4) battery</p> <p>Operating conditions: 0÷+45°C (32°F÷104°F), <90%RH</p>




Transit time



TTA

Accessories and spare parts for transit time flow meters



SGM-100S-520A004A	Fixing chain for transducers - price each mt
SGM-100S-525B007A	Connection cable for SGM-100F transducers - price each mt
SGM-100S-675C032A	Coupling gel for transducers
SGM-100S-870A002A	Tie rod for fixing chain
SGM-100S-909C001A	3 points calibration certificate
SGM-100S-909C002A	5 points calibration certificate
SGM-100S-S1-	Couple of clamp-on transducers DN 15-100
SGM-100S-S1F	Couple of transducers DN 15-100 on metric frame
SGM-100S-S1H	Couple of high temperature transducers (0÷150°C) for pipes from DN15 to DN100
SGM-100S-M1-	Couple of clamp-on transducers DN 50-700
SGM-100S-M1F	Couple of transducers DN 50-700 on metric frame
SGM-100S-M1H	Couple of high temperature transducers (0÷150°C) for pipes from DN50 to DN700
SGM-100S-L1-	Couple of clamp-on transducers DN 300-4000
SGM-100S-I1-	Couple of standard insertion transducers
SGM-100S-I2-	Couple of insertion transducers for cement pipes



SLM2X Total flow indicator with analog input

Suitable to be connected to analogic transmitters
 $4\div 20\text{mA}$ or $0\div 10\text{Vdc}$
 4 frontal push-buttons for calibration
 Data stored in EEPROM
 Working temperature: $-10^{\circ} \div +50^{\circ}\text{C}$
 Front panel mounting (dimA 92x45) IP54



Power supply	
00	115Vac
10	230Vac
20	24Vac
30	24Vdc
Version	
S206	Totalizzatore con display a 6 cifre



SLM2XH3 Total and instantaneous flow rate indicator with analog input

Suitable to be connected to analogic transmitters
 $4\div 20\text{mA}$ or $0\div 10\text{Vdc}$
 Removable 4 frontal push-buttons for calibration (optional)
 Data stored in EEPROM
 Working temperature: $-10^{\circ} \div +50^{\circ}\text{C}$
 Front panel mounting (dimA 92x45) IP54
 Accuracy: $0,005\% \pm 1$ digit
 Linearization: $0,005\% \pm 1$ digit

Power supply	
00	115Vac
10	230Vac
20	24Vac
30	24Vdc
Version	
S206	N.2 Display: 8 digit totalizer, 4 digits instantaneous flow rate
Optional (opt.)	
A	None
P	Removable 4 frontal push-buttons for calibration



Pressure



P-8

Pressure transmitter

Mechanical protection: IP65
 Operation temperature: $-10^{\circ} \div +80^{\circ}\text{C}$ (default)
 Power supply: 24Vdc
 Wire-loop connection (2-wire)
 Output signal: $4\div 20\text{mA}$ (min. 0,5mA, max. 30mA)
 "zero" and "full-scale" adjustment: $\pm 3\%$

Sensor type	
A1	Si-diffused sensor std.
A2	Ultra-stable
A3	With flat membrane
A4	With anti-corrosive membrane (Ta mat.)
B1	For high or low temperature: $-65^{\circ} \div +150^{\circ}\text{C}$ (only with M process connection)
Certification	
S	None
Process connection material	
1	Stainless Steel 316L
4	Hastelloy C
9	Special
Process connection	
A	Screw Thread 1/2NPT (small hole)
M	Screw Thread G $\frac{1}{2}$ " (small hole)
R	Screw Thread G $\frac{1}{2}$ " ($\varnothing 8\text{mm}$ big hole)
Y	Special (triclamp 1 $\frac{1}{2}$ " eur 60,00)
Sealed material	
1F	Fluorin Rubber: FPM (Viton)
2F	Butyl Rubber: IIR
4F	Fully Sealed Welding
Output	
2	$4\div 20\text{mA}$ 2-wires
9	Special
Display	
A	None
C	Digital LCD
Y	Digital LCD with 2 switch limited points
Z	Special
Accuracy	
2	$\pm 0,2\%$
5	$\pm 0,5\%$
9	Special



Pressure

93

Measure range	
A01	0 ÷ 20KPa (0 ÷ 0,2bar) absolute p.
A02	0 ÷ 25KPa (0 ÷ 0,25bar) absolute p.
A03	0 ÷ 30KPa (0 ÷ 0,3bar) absolute p.
A04	0 ÷ 35KPa (0 ÷ 0,35bar) absolute p.
A05	0 ÷ 40KPa (0 ÷ 0,4bar) absolute p.
A06	0 ÷ 60KPa (0 ÷ 0,6bar) absolute p.
A07	0 ÷ 100KPa (0 ÷ 1bar) absolute p.
A08	0 ÷ 160KPa (0 ÷ 1,6bar) absolute p.
A09	0 ÷ 200Kpa (0 ÷ 2bar) absolute p.
A10	0 ÷ 250Kpa (0 ÷ 2,5bar) absolute p.
A11	0 ÷ 400KPa (0 ÷ 4bar) absolute p.
A12	0 ÷ 600KPa (0 ÷ 6bar) absolute p.
A13	0 ÷ 1,0MPa (0 ÷ 10bar) absolute p.
A14	0 ÷ 1,6MPa (0 ÷ 16bar) absolute p.
A15	0 ÷ 2,0MPa (0 ÷ 20bar) absolute p.
A16	0 ÷ 2,5MPa (0 ÷ 25bar) absolute p.
A17	0 ÷ 4,0MPa (0 ÷ 40bar) absolute p.
A18	0 ÷ 6,0MPa (0 ÷ 60bar) absolute p.
A19	0 ÷ 10MPa (0 ÷ 100bar) absolute p.
G01	0 ÷ 4KPa (0 ÷ 0,04bar) gauge p. - without stainless steel membrane
G02	0 ÷ 6KPa (0 ÷ 0,06bar) gauge p. - without stainless steel membrane
G03	0 ÷ 10KPa (0 ÷ 0,1bar) gauge p.
G04	0 ÷ 16KPa (0 ÷ 0,16bar) gauge p.
G05	0 ÷ 20KPa (0 ÷ 0,2bar) gauge p.
G06	0 ÷ 25KPa (0 ÷ 0,25bar) gauge p.
G07	0 ÷ 30KPa (0 ÷ 0,3bar) gauge p.
G08	0 ÷ 35KPa (0 ÷ 0,35bar) gauge p.
G09	0 ÷ 40KPa (0 ÷ 0,4bar) gauge p.
G10	0 ÷ 60KPa (0 ÷ 0,6bar) gauge p.
G11	0 ÷ 100KPa (0 ÷ 1bar) gauge p.
G12	0 ÷ 160KPa (0 ÷ 1,6bar) gauge p.
G13	0 ÷ 200KPa (0 ÷ 2bar) gauge p.
G14	0 ÷ 250KPa (0 ÷ 2,5bar) gauge p.
G15	0 ÷ 400KPa (0 ÷ 4bar) gauge p.
G16	0 ÷ 600KPa (0 ÷ 6bar) gauge p.
G17	0 ÷ 1,0MPa (0 ÷ 10bar) gauge p.
G18	0 ÷ 1,6MPa (0 ÷ 16bar) gauge p.
G19	0 ÷ 2,0MPa (0 ÷ 20bar) gauge p.
G20	0 ÷ 2,5MPa (0 ÷ 25bar) gauge p.
G21	0 ÷ 4,0MPa (0 ÷ 40bar) gauge p.
G22	0 ÷ 6,0MPa (0 ÷ 60bar) gauge p.
G23	0 ÷ 10MPa (0 ÷ 100bar) gauge p.
G24	0 ÷ 20MPa (0 ÷ 200bar) gauge p.
G25	0 ÷ 30MPa (0 ÷ 300bar) gauge p.
G26	0 ÷ 40MPa (0 ÷ 400bar) gauge p.
G27	0 ÷ 60MPa (0 ÷ 600bar) gauge p.
G31	-20KPa ÷ +20KPa (-0,2 ÷ +0,2bar) gauge p.
G32	-50KPa ÷ +50KPa (-0,5 ÷ +0,5bar) gauge p.
G33	-100KPa ÷ +60KPa (-1 ÷ +0,6bar) gauge p.
G34	-100KPa ÷ +100KPa (-1 ÷ +1bar) gauge p.


Pressure



G35	-100KPa ÷ +150KPa (-1 ÷ +1,5bar) gauge p.
G36	-100KPa ÷ +300KPa (-1 ÷ +3bar) gauge p.
G37	-100KPa ÷ +500KPa (-1 ÷ +5bar) gauge p.
G38	-100KPa ÷ +900KPa (-1 ÷ +9bar) gauge p.
G39	-100KPa ÷ +1,5MPa (-1 ÷ +15bar) gauge p.
G40	-100KPa ÷ +2,0MPa (-1 ÷ +20bar) gauge p.
Z99	Special

Measured pressure

A	Absolute Pressure
B	Air-proof Reference Pressure (please provide reference pressure)
G	Gauge Pressure





Pressure


95

P-8J

Pressure transmitter

Mechanical protection: IP65
Operation temperature: $-40^{\circ} \div +85^{\circ}\text{C}$ (default)
Power supply: 24Vdc
Wire-loop connection (2-wires)

Certification	
S	None
Process connection material	
1	Stainless steel SS304
Process connection	
M	Screw thread $G\frac{1}{2}"$ (\varnothing 3mm hole)
Sealed material	
1F	Fluorine rubber: FPM (Viton)
Output	
2	4÷20mA , 2-wire
Display	
A	None
Accuracy	
5	±0,5%
Measure range	
G17	0 ÷ 1,0MPa (0 ÷ 10bar) (0 ÷ +100m) gauge p.
G18	0 ÷ 1,6MPa (0 ÷ 16bar) gauge p.
G19	0 ÷ 2,0MPa (0 ÷ 20bar) gauge p.
G20	0 ÷ 2,5MPa (0 ÷ 25bar) gauge p.
G21	0 ÷ 4,0MPa (0 ÷ 40bar) gauge p.
G22	0 ÷ 5,0MPa (0 ÷ 50bar) gauge p.
Measured pressure	
G	Gauge pressure



Pressure



P-K1

Pressure transmitter

Mechanical protection: IP67
 Operation temperature: $-10^{\circ} \div +80^{\circ}\text{C}$ (default)
 Power supply: 24Vdc
 Wire-loop connection (2-wires)
 Output signal: $4\div 20\text{mA}$ (min.0,5mA, max. 30mA)

Sensor type

A1	Si-diffused sensor std.
A2	Ultra-stable
A3	With flat membrane - fm 0,6bar (60KPa) to 10bar (1MPa)
A4	With anti-corrosive membrane (Ta)
B1	For high or low temperature ($-65^{\circ} \div +150^{\circ}\text{C}$)
B2	For high or low temperature ($-10^{\circ} \div +200^{\circ}\text{C}$)
C0	With ceramic capacitor

Certification

S	None
----------	------

Process connection material

1	Stainless Steel 316L
2	Stainless Steel 304
4	Hutchinson Alloy C
9	Special

Process connection

A	Male screw thread $\frac{1}{2}"\text{NPT}$ (small hole)
M	Male screw thread $G\frac{1}{2}"$ (small hole)
R	Male screw thread $G\frac{1}{2}"$ (big hole)
Y	Special

Sealed material

1F	Fluorin Rubber: FPM (Viton)
2F	Butyl Rubber: IIR
3F	Polyvinyl-4F: PTFE (Teflon) - Not for "A" type sensors -
4F	Fully sealed welding

Output

2	$4\div 20\text{mA}$ 2-wire
9	Special

Display

A	None
C	$0\div 100\%$ Digital LCD
Y	Special

Accuracy

1	$\pm 0,1\%$
2	$\pm 0,2\%$
5	$\pm 0,5\%$



Pressure

97


Measure range	
A01	0 ÷ 20KPa (0 ÷ 0,2bar) (0 ÷ 2000mm) absolute p.
A02	0 ÷ 25KPa (0 ÷ 0,25bar) (0 ÷ 2500mm) absolute p.
A03	0 ÷ 30KPa (0 ÷ 0,3bar) (0 ÷ 3000mm) absolute p.
A04	0 ÷ 35KPa (0 ÷ 0,35bar) (0 ÷ 3500mm) absolute p.
A05	0 ÷ 40KPa (0 ÷ 0,4bar) (0 ÷ 4000mm) absolute p.
A06	0 ÷ 60KPa (0 ÷ 0,6bar) (0 ÷ 6000mm) absolute p.
A07	0 ÷ 100KPa (0 ÷ 1bar) (0 ÷ 10m) absolute p.
A08	0 ÷ 160KPa (0 ÷ 1,6bar) (0 ÷ 16m) absolute p.
A09	0 ÷ 200KPa (0 ÷ 2bar) (0 ÷ 20m) absolute p.
A10	0 ÷ 250KPa (0 ÷ 2,5bar) (0 ÷ 25m) absolute p.
A11	0 ÷ 350KPa (0 ÷ 3,5bar) (0 ÷ 35m) absolute p.
A13	0 ÷ 1,0MPa (0 ÷ 10bar) (0 ÷ 100m) absolute p.
A14	0 ÷ 1,6MPa (0 ÷ 16bar) (0 ÷ 160m) absolute p.
A15	0 ÷ 2,0MPa (0 ÷ 20bar) (0 ÷ 200m) absolute p.
A16	0 ÷ 2,5MPa (0 ÷ 25bar) (0 ÷ 250m) absolute p.
A17	0 ÷ 4,0MPa (0 ÷ 40bar) (0 ÷ 400m) absolute p.
A18	0 ÷ 6,0MPa (0 ÷ 60bar) (0 ÷ 600m) absolute p.
A19	0 ÷ 10MPa (0 ÷ 100bar) (0 ÷ 1000m) absolute p.
G01	0 ÷ 4KPa (0 ÷ 0,04bar) (0 ÷ 400mm) gauge p. - without stainless steel membrane
G02	0 ÷ 6KPa (0 ÷ 0,06bar) (0 ÷ 600mm) gauge p. - without stainless steel membrane
G03	0 ÷ 10KPa (0 ÷ 0,1bar) (0 ÷ 1000mm) gauge p.
G04	0 ÷ 16KPa (0 ÷ 0,16bar) (0 ÷ 1600mm) gauge p.
G05	0 ÷ 20KPa (0 ÷ 0,2bar) (0 ÷ 2000mm) gauge p.
G06	0 ÷ 25KPa (0 ÷ 0,25bar) (0 ÷ 2500mm) gauge p.
G07	0 ÷ 30KPa (0 ÷ 0,3bar) (0 ÷ 3000mm) gauge p.
G08	0 ÷ 35KPa (0 ÷ 0,35bar) (0 ÷ 3500mm) gauge p.
G09	0 ÷ 40KPa (0 ÷ 0,4bar) (0 ÷ 4000mm) gauge p.
G10	0 ÷ 60KPa (0 ÷ 0,6bar) (0 ÷ 6000mm) gauge p.
G11	0 ÷ 100KPa (0 ÷ 1bar) (0 ÷ 10m) gauge p.
G12	0 ÷ 160KPa (0 ÷ 1,6bar) (0 ÷ 16m) gauge p.
G13	0 ÷ 200KPa (0 ÷ 2bar) (0 ÷ 20m) gauge p.
G14	0 ÷ 250KPa (0 ÷ 2,5bar) (0 ÷ 25m) gauge p.
G15	0 ÷ 400KPa (0 ÷ 4bar) (0 ÷ 40m) gauge p.
G16	0 ÷ 600KPa (0 ÷ 6bar) (0 ÷ 60m) gauge p.
G17	0 ÷ 1,0MPa (0 ÷ 10bar) (0 ÷ 100m) gauge p.
G18	0 ÷ 1,6MPa (0 ÷ 16bar) (0 ÷ 160m) gauge p.
G19	0 ÷ 2,0MPa (0 ÷ 20bar) (0 ÷ 200m) gauge p.
G20	0 ÷ 2,5MPa (0 ÷ 25bar) (0 ÷ 250m) gauge p.
G21	0 ÷ 4,0MPa (0 ÷ 40bar) (0 ÷ 400m) gauge p.
G22	0 ÷ 6,0MPa (0 ÷ 60bar) (0 ÷ 600m) gauge p.
G23	0 ÷ 10MPa (0 ÷ 100bar) (0 ÷ 1000m) gauge p.
G24	0 ÷ 20MPa (0 ÷ 200bar) (0 ÷ 2000m) gauge p.
G25	0 ÷ 30MPa (0 ÷ 300bar) (0 ÷ 3000m) gauge p.
G26	0 ÷ 40MPa (0 ÷ 400bar) (0 ÷ 4000m) gauge p.
G27	0 ÷ 60MPa (0 ÷ 600bar) (0 ÷ 6000m) gauge p.
G31	-20KPa ÷ +20KPa (-0,2 ÷ +0,2bar) (-2000 ÷ +2000mm) gauge p.
G32	-50KPa ÷ +50KPa (-0,5 ÷ +0,5bar) (-5000 ÷ +5000mm) gauge p.
G33	-100KPa ÷ +60KPa (-1 ÷ +0,6bar) (-10 ÷ +6m) gauge p.
G34	-100KPa ÷ +100KPa (-1 ÷ +1bar) (-10 ÷ +10m) gauge p.
G35	-100KPa ÷ +150KPa (-1 ÷ +1,5bar) (-10 ÷ +15m) gauge p.

Pressure



G36	-100KPa ÷ +300KPa (-1 ÷ +3bar) (-10 ÷ +30m) gauge p.
G37	-100KPa ÷ +500KPa (-1 ÷ +5bar) (-10 ÷ +50m) gauge p.
G38	-100KPa ÷ +900KPa (-1 ÷ +9bar) (-10 ÷ +90m) gauge p.
G39	-100KPa ÷ +1,5MPa (-1 ÷ +15bar) (-10 ÷ +150m) gauge p.
G40	-100KPa ÷ +2,0MPa (-1 ÷ +20bar) (-10 ÷ +200m) gauge p.
Z99	Speciale

Measured pressure	
A	Absolute pressure
B	Air-proof Reference Pressure(please provide reference pressure)
G	Gauge pressure





Pressure

P-L Hydrostatic head level transmitter

Measuring range: 0÷100m
Head connection mechanical protection: IP65
Probe mechanical protection: IP68
Cable material: PE
Operation temperature: -20° ÷ +70°C (default)
Power supply: 12/24Vdc
Wire-loop connection (2-wire)
Output signal: 4÷20mA (min.0,5mA, max. 30mA)

Version	
C-	Cable type (5m standard - max 25m); with connection head - Price each additional m
C1	Suspension type (5m standard cable); without connection head - Price each additional m
R-	Rod type (1m standard rod); with connection head - Price each additional m
Certification	
S	None
Process connection material	
1	Stainless Steel 316L (to be selected also for C1 version)
9	Special
Process connection	
T	Male Thread G 1" ½
Y	Special
Sensor type	
A-	Si-diffused sensor
A2	Ultra-stable
C-	Ceramic capacitor (not for C1 version)
Sealed material	
1F	Fluorin Rubber: FPM (Viton)
2F	Butyl Rubber: IIR
3F	Polyvinyl-4F: PTFE (Teflon) - For ceramic capacitance only
4F	Fully sealed welding
Output	
2	4÷20mA 2-wire
9	Special
Display	
A	None
C	Digital LCD
Y	Special
Accuracy	
1	±0,1% - only with ultra-stable sensor A2
2	±0,2%
5	±0,5%
9	Special
Counterweigh	
H	None



Measure range



G03	0 ÷ 10KPa (0 ÷ 0,1bar / 0 ÷ 1m H ² O) gauge p.
G04	0 ÷ 16KPa (0 ÷ 0,16bar / 0 ÷ 1,6m H ² O) gauge p.
G05	0 ÷ 20KPa (0 ÷ 0,2bar / 0 ÷ 2m H ² O) gauge p.
G06	0 ÷ 25KPa (0 ÷ 0,25bar / 0 ÷ 2,5m H ² O) gauge p.
G07	0 ÷ 30KPa (0 ÷ 0,3bar / 0 ÷ 3m H ² O) gauge p.
G08	0 ÷ 35KPa (0 ÷ 0,35bar / 0 ÷ 3,5m H ² O)
G09	0 ÷ 40KPa (0 ÷ 0,4bar / 0 ÷ 4m H ² O) gauge p.
G10	0 ÷ 60KPa (0 ÷ 0,6bar / 0 ÷ 6m H ² O) gauge p.
G11	0 ÷ 100KPa (0 ÷ 1bar / 0 ÷ 10m H ² O) gauge p.
G12	0 ÷ 160KPa (0 ÷ 1,6bar / 0 ÷ 16m H ² O) gauge p.
G13	0 ÷ 200KPa (0 ÷ 2bar / 0 ÷ 20m H ² O) gauge p.
G14	0 ÷ 250KPa (0 ÷ 2,5bar / 0 ÷ 25m H ² O) gauge p.
G15	0 ÷ 400KPa (0 ÷ 4bar / 0 ÷ 40m H ² O) gauge p.
G16	0 ÷ 600KPa (0 ÷ 6bar / 0 ÷ 60m H ² O) gauge p.
G17	0 ÷ 1,0MPa (0 ÷ 10bar / 0 ÷ 100m H ² O) gauge p.
Z99	Special



P-LC1.....



P-LR.....





Pressure

101

PAK

HART pressure transmitter

Mechanical protection: IP67
Operation temperature: $-20^{\circ} \div +70^{\circ}\text{C}$
Power supply: 24Vdc
Wire-loop connection (2-wire)
Output signal: $4 \div 20\text{mA}$ (min. 0,5mA, max. 30mA)

Sensor type	
A1	Si-diffused sensor std.
A2	Ultra-stable
A3	With flat membrane - fm 0,6bar (60KPa) to 10bar (1MPa)
A4	With anti-corrosive membrane (TA)
B1	For high-low temperature ($-65^{\circ} \div +150^{\circ}\text{C}$)
B2	For high-low temperature ($-10^{\circ} \div +200^{\circ}\text{C}$)
C0	Ceramic capacitor
C1	Metal-ceramic capacitor
Certification	
D	ATEX II 2 G Exd II C T6 (PENDING)
I	Intrinsic safety EEx ia IIC T6 or EEx ib IIC T6
S	None
Process connection material	
1	Stainless Steel 316L
2	Stainless Steel 304
4	Hutchinson Alloy C
9	Special
Process connection	
A	Male screw thread $\frac{1}{2}"$ NPT (small hole)
M	Male screw thread $G\frac{1}{2}"$ (small hole)
R	Male screw thread $G\frac{1}{2}"$ (big hole)
Y	Special
Sealed material	
1F	Fluorin rubber: FPM (Viton)
2F	Butyl Rubber: IIR
3F	Polyvinyl-4F: PTFE (Teflon)
4F	Fully sealed welding
Output	
I	$4 \div 20\text{mA}$ 2-wire HART
Y	Special
Display	
A	None
C	LCD digital
Y	Special
Accuracy	
1	$\pm 0.1\%$ (only with A2 ultra-stable sensor or C1 metal-ceramic capacitor)
2	$\pm 0.2\%$
5	$\pm 0.5\%$
7	$\pm 0.075\%$ (only with C1 metal-ceramic capacitor)

Pressure



Measure range


A03	0÷1...6kPa (0÷0,01...0,06 bar) (0÷100...600 mm H ₂ O) - only for A2 sensor (ultra-stable)
A04	0÷10...40kPa (0÷0,1...0,4 bar) (0÷1000...4000 mm H ₂ O) - for sensors type A/B
A05	0÷40...200kPa (0÷0,4...2 bar) (0÷4...20 m H ₂ O) - for sensors type A/B
A06	0÷160kPa...1.0MPa (0÷1,6...10 bar) (0÷16...100 m H ₂ O) - for sensors type A/B
A07	0÷0,4...2MPa (0÷4...20 bar) (0÷40...200 m H ₂ O) - for sensors type A/B
A08	0÷1,8...4MPa (0÷18...40 bar) (0÷180...400 m H ₂ O) - for sensors type A/B
A09	0÷3,8...20MPa (0÷38...200 bar) (0÷380...2000 m H ₂ O) - for sensors type A/B
A10	0÷10...60MPa (0÷100...600 bar) (0÷1000...6000 m H ₂ O) - only for A2 sensor (ultra-stable)
C03	-5 ÷ +5kPa (-0,05 ÷ +0,05 bar) (-500 ÷ +500 mm H ₂ O) - for sensor type C0
C04	-50 ÷ +50kPa (-0,5 ÷ +0,5 bar) (-5000 ÷ +5000 mm H ₂ O) - for sensor type C0
C05	-100 ÷ +100kPa (-1 ÷ +1 bar) (-10 ÷ +10 m H ₂ O) - for sensor type C0
C06	-100 ÷ +300kPa (-1 ÷ +3 bar) (-10 ÷ +30 m H ₂ O) - for sensor type C0
C07	-100 ÷ +900kPa (-1 ÷ +9 bar) (-10 ÷ +90 m H ₂ O) - for sensor type C0
C08	-100kPa ÷ +2.0MPa (-1 ÷ +20 bar) (-10 ÷ +200 m H ₂ O) - for sensor type C0
C14	0÷6...40kPa (0÷0,06...0,4 bar) (0÷600...4000 mm H ₂ O) - for sensor type C1
C15	0÷40...200kPa (0÷0,4...2 bar) (0÷4...20 m H ₂ O) - for sensor type C1
C16	0÷160kPa...1.0MPa (0÷1,6...10 bar) (0÷16...100 m H ₂ O) - for sensor type C1
C17	0÷0,4...2,5MPa (0÷4...25 bar) (0÷40...250 m H ₂ O) - for sensor type C1
C18	0÷1,6...10MPa (0÷16...100 bar) (0÷160...1000 m H ₂ O) - for sensor type C1
C19	0÷4...20MPa (0÷40...200 bar) (0÷400...2000 m H ₂ O) - for sensor type C1
Z99	Special

Measured pressure

A	Absolute pressure
B	Air-proof reference pressure (please provide value)
G	Gauge pressure

Optional (opt.)

A0	None
B2	Bending bracket for panel installation
B3	Flat bracket for 2" pipe installation
Z9	Special





Pressure

103

P-BADP

"General purpose" differential pressure transmitter

HART Communication: IP67

Operation temperature: -40° ÷ +85°C




Power supply: 24Vdc

Mechanical protection: IP67


Standard connection: NPT 1/4"

Measure range				
3	0÷1...6kPa (0÷0,01....0,06 bar) (0÷100....600 mm H²O) - Max pressure 4MPa			
4	0÷6...40kPa (0÷0,06....0,4 bar) (0÷600....4000 mm H²O) - Max pressure 10MPa			
5	0÷40...200kPa (0÷0,4....2 bar) (0÷4....20 m H²O) - Max pressure 10MPa			
6	0÷160...700kPa (0÷1,6....7 bar) (0÷16....70 m H²O) - Max pressure 10MPa			
7	0÷0.4...2MPa (0÷4....20 bar) (0÷40....200 m H²O) - Max pressure 10MPa			
8	0÷1.6...6.8MPa (0÷16....68 bar) (0÷160....680 m H²O) - Max pressure 10MPa			
Output				
I	4÷20mA/HART (linear)			
J	4÷20mA/HART (square root)			
Construction materials				
22	Flange /Adapter 316 SST	Drain/Vents 316 SST	Diaphragm 316 SST	Filling liquid Silicon
23	Flange/Adapter 316 SST	Drain/Vents 316 SST	Diaphragm Hastelloy C	Filling liquid Silicon
Certification				
D	ATEX II 2 G Exd II C T6			
I	Intrinsic safety EEx ia IIC T6 or EEx ib IIC T6			
S	None			
Accuracy				
7	±0.075%			
Optional (opt.)				
B1-	Bending bracket 90° for max 2"pipe installation, carbon steel			
B2-	Bending bracket 90° for panel installation, carbon steel			
B3-	Flat bracket for max 2"pipe installation, carbon steel			
C12	Flange for 1/2" NPT connection + 1/2" NPT welding connection			
D0-	Fore-end drain/vent - >STANDARD<			
D1-	Side drain/vent, top			
D2-	Side drain/vent, bottom			
J--	Male thread m20x1.5			
M3-	LCD display			
N--	1/2" NPT flange			
O--	Nr. 2 PTFE O-ring			
Z99	Special			

Pressione



Range code	2x - 3 - 4 - 5	6	7	8
A (mm)	54	55.2	55.6	57.2



P-BADR

Low ranges differential pressure transmitter

HART Communication - IP67

Operation temperature: -40° ÷ +85°C

Power supply: 24Vdc

Mechanical protection: IP67

Standard connection NPT 1/4"

Measure range	
2A	0÷0.16...1.6kPa (0÷0,0016...0,016 bar) (0÷16...160 mm H ₂ O) - Max static pressure 1MPa
2B	0÷0.16...1.6kPa (0÷0,0016...0,016 bar) (0÷16...160 mm H ₂ O) - Max static pressure 2.5MPa
2C	0÷0.16...1.6kPa (0÷0,0016...0,016 bar) (0÷16...160 mm H ₂ O) - Max static pressure 4MPa
Output	
I	4÷20mA/HART (linear)
J	4÷20mA/HART (square root)
Construction materials	
22	Flange /Adapter 316 SST Drain/Vents 316 SST Diaphragm 316 SST Filling liquid Silicon
23	Flange/Adapter 316 SST Drain/Vents 316 SST Diaphragm Hastelloy C Filling liquid Silicon
Certification	
D	ATEX II 2 G Exd II C T6
I	Intrinsic safety Ex ia IIC T6 or Ex ib IIC T6
S	None
Accuracy	
7	±0.075%
Optional (opt.)	
B1-	Bending bracket 90° for max 2"pipe installation, carbon steel
B2-	Bending bracket 90° for panel installation, carbon steel
B3-	Flat bracket for max 2"pipe installation, carbon steel
C12	Flange for 1/2" NPT connection + 1/2" NPT welding connection
D0-	Fore-end drain/vent - >STANDARD<
D1-	Side drain/vent, top
D2-	Side drain/vent, bottom
J--	Male thread m20x1.5
M3-	LCD display
N--	1/2" NPT flange
Z99	Special

Pressure



PA

Pressure and differential pressure system accessories

Optional (opt.)	
010E106A	HART communication software for P-AK/BADP/BADR
199-2150	2 valves bar stock manifold - 1/2" NPT- F
199-3150	3 valves bar stock manifold - 1/2" NPT- F
199-3451	3 valves forged manifold - 1/2" NPT- F
835A001A	Cable anchoring clamps
902A013A	3 points calibration certificate
902A014A	5 points calibration certificate
902A015A	Customer calibration
P-8S-C***	LCD digital display for P-8 model
P-8S-Y***	LCD digital display with 2 switch limited points for P-8 model
P-BADS-M3	LCD digital display for P-BADP / P-BADR models



Temperature

107



AGRITHERM3 Manual display unit for small plants

Wall-mounting - IP55

Manual system for mounting of max. 3 multipoints TT probes.

All probe points displayed for each mounted probe, through the relevant pushing buttons

Version	
A	Standard
Power supply	
1	Battery - 4x1,5V AAA
2	230Vac 50÷60Hz
Accessories	
A	None
B	AGW-FTP connecting cable (Probe/MUX/Agritherm) + sheat (price each meter)



AGRITHERM10 Display and control unit

For all MUX type connection



Manual/automatic selection

4 pushbuttons keyboard for programming, 5+1 LED digits display, panel mounting std.48x96 IP40

Factory programmable configuration of: MUX..., transducers, measur.point, etc.

n.2 alarm relays

Version	
A	Base
Power supply	
1	115Vac 50÷60Hz
2	230Vac 50÷60Hz
Accessories	
A	None
M	Frontal protection windows IP54
Z	Special



Temperature



AGRITHERM20 Display and control unit

IP66 unit for all MUX type connection
 Manual or automatic management
 128x64 back-lighted LCD display, 4 keys for programming
 Programmable configuration of: MUX..., transducers, measur.point, alarms, etc.
 Up to 5 relays fully programmable
 RS485 Output

Relay	
C	N.5 SPDT relays
Power supply	
0	115Vac 50+60Hz
1	230Vac 50+60Hz
2	24Vac 50+60Hz
Output	
A	None
Z	Special
Field Bus	
0	RS485
9	Special



AGRITHERM40 PC based for temperature display and control


Suitable for MUX.. connection
 Manual or automatic management
 Video pages temperature display, alarms management
 PC keyboard and long distance communication converter RS232/RS485
 Programmable configuration of: MUX..., transducers, measur.point, alarms, etc.
 Power supply, 230Vac

Version	
A	Standard: HD 80GB; RAM DDR400 256MB; 19" LCD monitor
B	With relays board mod. 199DASP52016 (only with SGM PC)
Z	Special
Accessories	
0	None
1	USB ink jet printer
9	Special



Temperature

109



Temperature



MUX

Concentrator suitable for up to 8 TT rope probe connection

Output RS485 for sistem modules communication


Power supply : 230V 50Hz

Visualization ON-BOARD of Max. 12 points

Suitable for the connection to AGRITHERM units for display of 12 points

Version	
01	IP66 polycarbonate enclosure with cable glands (not certificable)
02	IP66 aluminum enclosure with cable glands (ATEX certificable)
99	Special (not certificable)

Certification	
AA	None
Ex	ATEX II 2(1) D IP66 T125°C





Temperature

111

TT

Digital multipoints temperature rope probe

SS304 flexible well

Up to 12 measurement points distributed into the probe length, displayed on the MUX unit

Temperature range -30 +125°C

Accuracy +/- 0,5°C from -10 to + 85°C

Version	
1	IP66 diecast aluminum varnished (DIN-B)
9	Special
Process connection	
A	1/2" SS threaded
B	Under roof fixing + 1m chain and accessories
C	1/2" SS thread + DN40 PN6 carbon steel flange
Z	Special
Well, price each meter	
0L	Ø7÷8mm Flexible SS304 pipe, length = ____m
99	Special
Temperature sensor n.	
00	None
01	N. 1 measurement point
02	N. 2 measurement points
03	N. 3 measurement points
04	N. 4 measurement points
05	N. 5 measurement points
06	N. 6 measurement points
07	N. 7 measurement points
08	N. 8 measurement points
09	N. 9 measurement points
10	N. 10 measurement points
11	N. 11 measurement points
12	N. 12 measurement points
99	Special
xx	Euro 17,00 for each measurement point over 12th
Certification	
A	None
B	ATEX II 1 D IP66 T125°C
C	ATEX 22 Zone
Accessories	
0	None
2	Sensor, mounted into the connection head
9	Special



Temperature



TA AGRITHERM system accessories

Optional (opt.)	
010D076A	1.01 AGRITHERM40 software for PC (Ita-Eng-Fra)
010D076B	1.04 AGRITHERM40 software for PC (Ita-Eng-Fra)
010D076C	1.04 AGRITHERM40 software for PC (Russian)
525B003A	FTP 4x2x24 AWG connection cable, price per meter
694A003A	RS485/RS232 converter module with 9 pins comm. Port
694A004A	RS485/RS232 converter module with USB port
902A005A	Agritherm configuration or modification made in factory

TSP AGRITHERM system spare parts

Spare parts	
350A001A	Mother Board MUXA
350A003A	Mother Board MUXC
350A004A	Mother Board MUXD
350A010A	Mother Board MUX



ATEX



KEMA CERTIFICATE



ISO 9001:2008

DUTCH COUNCIL FOR ACCREDITATION C 013



al servizio dell'applicazione

SGM LEKTRA s.r.l.

Via Papa Giovanni XXIII, 49
20090 Rodano (Milano)

tel. ++39 0295328257 r.a.

fax ++39 0295328321

e-mail: info@sgm-lektra.com

www.sgm-lektra.com

Mod. 734B006H - documentation subject to technical change with no prior warning -

